

S.N	Material	UoM	Material class	Long Description
1	727101	EA	SENSOR	SENSOR: TYPE CARBON MONOXIDE, RANGE 0-500 PPM, FFT: 0 TO 500 PPM CARBON MONOXIDE SENSOR FOR DETECTIVE PORTABLE DETECTOR, Mfnr: CROWCON DETECTION INSTRUMENTS LTD Mfnr Part No: S011368, Model/Machine No: DETECTIVE
2	488860		MOTOR, GEARED	MOTOR, GEARED: POWER RATING: 2.2 51 KW, ELECTRICAL RATING: 266/460VAC 7.30/4.25A 60HZ, PHASE: 3 PH, OUTPUT SPEED: 125 RPM, RATIO: 13.73:1, GEARBOX TYPE: SA67, ENCLOSURE: IP55; FFT: TYPE SA67/TDV 100M4/BMG/NV12; FOR GEAR BRAKE OF LOADING PLATE MOTOR, POS P+60M1, 3" IEC 34, I = 13.73:1, 1710/125 RPM, 154 NM, 0.83 PF, IM M1A, 63.91 KG, IP 55, INSUL CL H, BRAKE : 266 VAC, 24 NM, BSR, STANDARD : IEC 34; P/N: SA67/TDRN100M4/BES/E172, Mfnr: SEW EURODRIVE, REFERENCE: COMM NO 17891, SERIAL: 01.300831913.00010X, Mfnr: SEW EURODRIVE, DPL-10405221-SB, POS: POS 1.1
3	244789	EA	PLUG	PLUG: TYPE SCREW, MATERIAL STEEL, FFT: FOR 720-T-07/08 MDL CF 465 SER NO 4.244.481/482, Mfnr: KKK P/N: 00035252703, DRAWING: 49501100321 Rev: 0 Item: 110.070
4	1553802	EA	MOTOR, ELECTRIC	MOTOR, ELECTRIC: POWER RATING: 0.75 KW, ELECTRICAL RATING: 266/460VAC, 2.70/1.56A, 60HZ, SPEED: 1751/145 RPM, MOUNT: BR, ENCLOSURE: IP55, INSULATION CLASS: H, PHASE: 3, FFT: FOR INFEED BELT OF GEAR BRAKE, POS NO: P+40M1, 1-TYPE: SA47/TDRN80M4/BE1, 3" IEC 34, I : 12.10:1, 46 NM, BRAKE : 266 V / 7; P/N: SA47/TDRN80M4/BE1 (NEW MODEL), Mfnr: SEW EURODRIVE, DRAWING: GPL-1806002-4C, POS: POS 1.1, DPL-1806002-4C, POS: 1.1
5	214518	ST	CONTROLLER, ELECTRONIC	CONTROLLER, ELECTRONIC: TYPE TEMPERATURE, MOUNT PANEL, ELECTRICAL RATING 264VAC 8.5W 48/62HZ, STANDARD UL, FFT: FOR PRESS Moulding MACHINE MODEL-SB334C6-11-M4 EQUIP NO-95-10-009 DIGITAL DISPLAY IN DEG F, PROGRAMMABLE ENROLHERM 818, Mfnr: PHILADELPHIA GEAR CORPORATION, USA Mfnr Part No: 818, Mfnr: EURO THERM CONTROLS Mfnr Part No: 818P4, Mfnr: A & G INSTRUMENT SERVICES Mfnr Part No: 818P4
6	569642	EA	TACHOMETER	TACHOMETER: TYPE DIGITAL PROCESS, RANGE 0-25000 RPM, RATING 120VAC 60HZ, FFT: SPEED TRANSMITTER WITH 4 SPOT RELAY OUTPUTS, INPUT SIGNAL TACHOMETER PICKUP, OUTPUT 4-20MA DC, OUTPUT READOUT 0-1 MM, TAGP 31-ST-3010A / B, OEM: ROTOFLOW CORPORATION INC OEM Part No: 6965025136, Mfnr: AIRPAX Mfnr Part No: 777430-11
7	885831	EA	MOTOR, GEARED	MOTOR, GEARED: ELECTRICAL RATING 440VAC 60HZ, RATIO 1/30, FFT-POLE: 4; MATERIAL: POLYURETHANE; FOR ROTARY VALVE, Mfnr: PELLETRON CORPORATION MNFR PART NO: SW-14, SUPPL: DONG YANG P & F SUPPL PART NO: UNK, TEST CERTIFICATE COMMENTS: ROUTINE MOTOR TEST CERTIFICATE
8	1580047	EA	ACTUATOR, PNEUMATIC	ACTUATOR, PNEUMATIC: TYPE CYLINDER, PRESSURE RATING 700 KPA, OPERATED AIR, BENCH RANGE 300 - 700 KPA, MOUNT BASE, INLET CONNECTION TYPE 1/2 NPT FOR CYLINDER AIR CONNECTION, APPLICATION CHILLED WATER COMPRESSOR DAMPER ACTUATOR, Mfnr: SMC CORPORATION MNFR PART NO: CPS1 LN 125-100KY
9	964567	EA	CONNECTOR, ELECTRICAL	CONNECTOR, ELECTRICAL: FFT: FOR DCR NO. 03-301, Mfnr: SCHAEVITZ Mfnr Part No: 62101011-000, Reference No: BNDX PT06A-10-65, Model/Machine No: LVDT-HCT-15-250
10	677049	EA	BREAKER, CIRCUIT	BREAKER, CIRCUIT: VOLTAGE 480 VAC, POLE 3, AMPERAGE 70 A, Mfnr: WESTINGHOUSE ELECTRICAL CORPORATION Mfnr Part No: EHB3070
11	559021		CONVERTER	CONVERTER: TYPE LOAD CELL, FFT-MODEL NO.: LC 400; FOR TAG 06-JHW-0351/0352/0353/0354/0355 03-JHW-0356/0357/0358 & 03-JHW-0371
12	991956	SE	KIT, ACTUATOR REPAIR	KIT, ACTUATOR REPAIR, TYPE: REPLACEMENT, COMPRISING: COVER GASKET, NON ASBESTOS, P/N-2.1, QTY:1; YOKE SEAL, BUNA-N, P/N-3.1, QTY:2; SNAP RING, SPRING STEEL, P/N-6.2, QTY:2; TOP BUSHING SEAL, BUNA-N, P/N-7.1, QTY:1; DA ADJUST SEAL, BUNA-N, P/N-9.1, QTY:2; HOUSING SIDE GASKET, NON ASBESTOS, P/N-12.0, QTY:2; HEAD FLANGE OUT SEAL, BUNA-N, P/N-16.1, QTY:1; HEAD FLANGE SEAL, PTFE+BUNA-N, P/N-16.3, QTY:2; PISTON SEAL, BUNA-N, P/N-18.1, QTY:1; PISTON INNER ROD SEAL, BUNA-N, P/N-18.3, QTY:1; BOTTOM FLANGE OUT SEAL, BUNA-N, P/N-20.1, QTY:1; SPRING END COVER SEAL, BUNA-N, P/N-30.1, QTY:1; SR ADJUST SEAL, BUNA-N, P/N-31.1, QTY:1; NAMUR BRACKET SEAL, QTY-8, APPLICATION: BUTTERFLY ON-OFF VALVE; Mfnr: FLOWBUS CORPORATION, SERIAL: SB62C-19-5294-0; Mfnr DRG: EPT106-295-5
13	968507	EA	FAN	FAN; TYPE: COOLING, SIZE: 68.5 MM, ELECTRICAL RATING: 115V 60HZ 65W, MOUNT: EXTERNAL, MATERIAL: PLASTIC; FFT: WITH 6 MICRO FARAD CAPACITOR STANDARD - IEC; P/N: R2E190-RASD-21, Mfnr: EBM PAPST
14	151866	EA	RELAY, PNEUMATIC	RELAY, PNEUMATIC: TYPE VOLUME BOOSTER, INPUT / OUTPUT CONNECTION FNPT 1/4 IN, MOUNT BRACKET/SURFACE, SUPPLY CONNECTION FNPT 1/4 IN, Model/Machine No: 61H Mfnr: MOORE PRODUCTS CO, Reference No: B/M 10342/23PH Mfnr: MOORE PRODUCTS CO
15	258778	EA	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC: TYPE FEED AIR PRESSURE, INLET PRESSURE: MAX 1000 KPA, OUTLET PRESSURE: MAX 400 KPA, CONNECTION: (7) FNPT 1/4 IN; FFT: FOR INSTRUMENT AIR SUPPLY, FOR VALMET PROCESS AUTOMATION, WITH GAUGE 0-2.5BAR; P/N: FAIRCHILD (MODEL 30) - PN: 30242 + WIKA - PN: 9690225, REFERENCE: FEED AIR, Mfnr: VALMET
16	1661715	EA	CONTROLLER, ELECTRONIC	CONTROLLER, ELECTRONIC: TYPE: PID, RANGE: -40 TO 158 DEG F (-40 TO 70 DEG C), INPUT: 12 UNIVERSAL INPUTS, OUTPUT: 8 BINARY OUTPUTS, MOUNT: FRAME, SIZE: L 373 X H 418 X W 140 MM, APPLICATION: HVAC; FFT: COMPLETE WITH THE ENCLOSURE, DISPLAY AND TRANSFORMER; SUPPLIER TO SEND PRE-CONFIGURED CONTROLLER; P/N: BMT000A00A01, Mfnr: TRANE
17	1658472	ASV	THERMOCOUPLE	THERMOCOUPLE; TYPE: K DUAL, TEMPERATURE RANGE: 0 TO 400 °C, SHEATH DIAMETER: 1/4 IN, SHEATH MATERIAL: 316 SS, HEAD: AL, JUNCTION: DUPLEX GROUNDED, OVERALL LENGTH: 15.5 IN; FFT: WITH GATE VALVE, GATE VALVE SIZE: 1/2 IN, RATING: 300 LB, MATERIAL: SS316L, CONNECTION: SOCKET WELD/THREADED ENDS, TEST CERTIFICATE COMMENTS: LEAK TEST CERTIFICATE IS REQUIRED HEAD: ALUMINUM EXPLOSION PROOF SCREW COVER HEAD; OEM: DAILY THERMETRICS; DRAWING: 344-F7AM06-198
18	1050207	SE	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC: TYPE PRESSURE, CONNECTION THREADED, BODY SIZE 1/4 IN, BODY MATERIAL ALUMINUM DIE CASTING, FFT: WITHOUT BACKFLOW FUNCTION, PORT SIZE: 1/4 IN, WITH BRACKET, WITH PRESSURE GAUGE, RC THREADED CONNECTION, OEM: SMC CORP. OEM PART NO: AW20-02BG-B, SERIAL NO: UC315M10A-14M4D
19	1036848		MOTOR, GEARED	MOTOR, GEARED: ELECTRICAL RATING: 400VAC 21.60A 150HZ, PHASE: 3, OUTPUT SPEED: 3000/560 RPM, GEARBOX TYPE: HELICAL-BELT, ENCLOSURE: IP65; FFT: 840; MAX. INPUT SPEED: 4500RPM; MAX. OUTPUT TORQUE : 199 NM; INCLUDING RETRO FIT KIT, FOR NEW BAGGING AND TRUCK LOADING MACHINE LINE.; P/N: 35068135, Mfnr: SEW EURODRIVE, MODEL: KA371 C/MP63M/8P/KY/RH1M/SB1
20	652592	ST	RELAY	RELAY: CONTACT RATING 120VAC 10A, CONTACT ARRANGEMENT 2NO-2NC, ACTION DPDT, COIL VOLTAGE 24 VDC, TERMINAL (8) PIN ROUND, MOUNT PLUG IN, ENCLOSURE HERMETICALLY SEALED, STANDARD CSA; UL, FFT: SOURCE: RELAY, Mfnr: POTTER & BRUMFIELD/TYCO ELECTRONICS Mfnr Part No: KR-11DGE-24, SPR: U80-070-1 Rev: 0 Item: NONE
21	655588	EA	REDUCER, CONDUIT	REDUCER, CONDUIT: SIZE 3/4 X 1/2 IN, FFT: ZERO IN OLD MATERIAL NO: 02-02-00217
22	970462	EA	CIRCUIT	CIRCUIT: TYPE THREE PHASE CURRENT CONTROLLER, APPLICATION CORROSION PROTECTION SYSTEM, FFT: 40VDC, 55A DC, Mfnr: CORROSION SERVICE CO LTD Mfnr Part No: TRPC-40-55-480-CB
23	1554101	EA	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC: TYPE AIR FILTER REGULATOR, INLET PRESSURE 8 BAR, OUTLET PRESSURE 0 TO 8 BAR, CONNECTION 3/8 NPT, BODY MATERIAL METAL BOWL WITHOUT SIGHT GAUGE, FFT: GLOBAL MODULAR COMPACT FILTER REGULATOR; AUTO DRAIN, METAL BOWL WITHOUT SIGHT GAUGE, OEM: PARKER OEM PART NO: P32EA93EMANBGP, CATALOGUE PDN1000-3US_P3_FILTER-REGULATOR REV: 0 ITEM NO: 1, DRG CA-K-2102B REV: 4 ITEM NO: CAH213V
24	770178	KIT	KIT, CABLE JOINT	KIT, CABLE JOINT: ELECTRICAL RATING 8 KV, CONDUCTOR 240 MM2, FFT: SPLICE TYPE, FOR 3/C 8KV SHIELDED ARMORED CABLE, SHD-GC, 3/C 240 MM2 (500 MCM) WITH 2 GROUND CONDUCTOR AND 1 INSULATED GROUND CHECK CONDUCTOR, COMPLETE WITH HEAT SHRINKABLE WRAPAROUND SLEEVE, INCLUDING TUBES, STRESS RELIEF MATERIAL FOR WRAPPING AROUND CONDUCTORS AND CHANNEL CLIP, WITH STEP-BY-STEP ASSEMBLY, Mfnr: RAYCHEM TYCO CORPORATION Mfnr Part No: RYSA-3-8245
25	1614887	EA	SWITCH, LIMIT	SWITCH, LIMIT: FFT: WITH INDUCTIVE LIMIT SENSORS SB3-5-E2
26	845487	EA	TRANSFORMER	TRANSFORMER: PRIMARY VOLTAGE 360/460 V, FFT: FOR PACKAGE UNIT, Mfnr: LIEBERT CORPORATION Mfnr Part No: 159463P2, Equip/Tag Model No: ET048SRA00A5117, Equip/Tag Serial No: 873117-002, 873117-005
27	957517	EA	TIMER	TIMER: TYPE FORCE FEED LUBRICATOR DIGITAL NO FLOW, CONTACT RATING 240VDC 2.5VA, RANGE 3 MIN, STANDARD CE, FFT: WITH PROXIMITY SWITCH; FOR TRABON DISTRIBUTION BLOCKS, DC; S/D, Mfnr: ARIEL CORPORATION, USA Mfnr Part No: A-10753
28	677656	EA	GAUGE, PRESSURE	GAUGE, PRESSURE: RANGE 0-7BAR; 0-700KPA; 0-100PSI, DIAL SIZE 2 IN, CONNECTION MNPT 1/4 IN, CONNECTION LOCATION LOWER, MOUNT STEM, FILLED NON
29	548211	EA	THERMOMETER, DIAL	THERMOMETER, DIAL: TYPE BI-METALLIC, RANGE 0-450 DEG C, DIAL SIZE 120 MM, CONNECTION MNPT 1/2 IN, CONNECTION LOCATION BACK/REAR, Mfnr: TREND INSTRUMENT INC, USA Mfnr Part No: CRS127C, Model/Machine No: 52-120 Mfnr: TREND INSTRUMENT INC, USA
30	22958	ST	BALLAST	BALLAST: VOLTAGE 120 VAC, WATTAGE 250 W, LAMP HPM, FFT: COMPLETE WITH MOUNTING KIT, Mfnr: ADVANCE TRANSFORMER CO. Mfnr Part No: 71A3527-001
31	437372	EA	DIAPHRAGM	DIAPHRAGM: MATERIAL EPDM, FFT: FOR EOP-10-TV-3162, MDL-4 IN X33-37412, SN:3129A1607-7, 30, Mfnr: NIGATA MASONEILAN CO LTD Mfnr Part No: 041103020D, Mfnr: WEATHERFORD Mfnr Part No: UNKNOWN, DRAWING: 041103-020-D Rev: 0
32	37799	EA	METER, FLOW	METER, FLOW: TYPE AIR, CONNECTION FNPT 1/8 IN, RANGE 0/0.7-7.60 L/MIN, MATERIAL SS, FFT: WITH NEEDLE VALVE; TUBE R-2-15-C; DESIGN RATING 200PSIG AT 250DEG F, Mfnr: BROOKS INSTRUMENT DIV. Mfnr PART NO: NEW: 1355GACB8F1A00A, Mfnr: BROOKS INSTRUMENT DIV. Mfnr PART NO: OLD: 1355EE2B8FF1A, Mfnr: RESCO Mfnr PART NO: OLD: 1355EE2B8FF1A
33	934341	KIT	BALLAST	BALLAST: TYPE: HIGH PRESSURE MERCURY LAMP, VOLTAGE: 120/208/240/277 V, AMPERAGE: 1.60/1.00/0.80/0.70 A, WATTAGE: 150 W, BALLAST STYLE: MAGNETIC PULSE, LAMP: METAL HALIDE, STANDARD: ANSI M81; FFT: SIZE: WD - 2.13/16 X LG 3-15/16 IN; P/N: 47229-C, SUPPL: OSRAM
34	510273	EA	ROPE, WIRE	ROPE, WIRE: DIAMETER: 14 MM, STRENGTH: 248 KN, MATERIAL: GALVANIZED WIRE, OVERALL LENGTH: 150 M, ROPE TYPE: LEFT HAND LAY, FFT: FOR OVERHEAD COMP. HOUSE CRANE, 14.0-8X26-B-LHO-194.8; P/N: (OLD) KP7D9020 (NEW) 56060957, Mfnr: KCI KONECRANES PLC; DRAWING: ROPE DRUM SHEET - 5, POS: 10; TEST CERTIFICATE COMMENTS: WIRE ROPE TEST CERTIFICATE
35	1524536	EA	CONTROLLER	CONTROLLER: TYPE TEMPERATURE, RANGE SENSOR LIMITED 2000 °C, RATING 50 TO 70 HZ, 3 VA, APPLICATION TO CALCULATE OPTIMUM PID VALUES, INPUT 100-240 V AC, SIZE 24 H X 48 W X 10 D MM, Mfnr: OMEGA Mfnr Part No: CN132
36	1677529	ML	STANDARD	STANDARD; TYPE: LIQUID MIXTURE CALIBRATION, MATERIAL: BTEX 200 MG/ML EACH IN P&T METHANOL, CONTAINER CAPACITY: 1 ML, PHYSICAL FORM: LIQUID, CONTAINER TYPE: CHEMICAL GLASS AMPUL; CAS NO: 108-88-3, CHEMICAL NAME: TOLUENE, CAS NO: 71-43-2, CHEMICAL NAME: BENZENE; FFT: HEADSPACE GC FOR VOC APPLICATION; P/N: 30051, Mfnr: RESTEK CORPORATION; TEST CERTIFICATE COMMENTS: MTC TO ACCOMPANY WITH THE DELIVERY ; HAZARDOUS IDENTIFICATION: H340 MAY CAUSE GENETIC DEFECTS. H350 MAY CAUSE CANCER
37	7138120	EA	UNIT CONTROL	UNIT CONTROL: TYPE RELAY TEST INPUT 115/230VAC 50/60HZ OUTPUT VOLTAGE 250VAC/300VDC CURRENT OUTPUT-0 TO 100A SUPPLY 115V/230 VAC/50/60 HZ VAC STANDARD CE FFT: USED FOR SECONDARY TESTING OP PROTECTIVE RELAYS Mfnr: PROGRAMMA TORKE Mfnr Part No: SVERKER 760 Tag/Equip No: U&O SATELLITE WS TOOL LIST IN Mfnr: UNKNOWN
38	7349986	EA	Software	SOFTWARE TYPE: LAB NAME: EASYMATCH QC FORMAT: CD COMPATIBILITY: WINDOWS 10 FFT: COME WITH PC OS WINDOWS 10 PROFESSIONAL 8 GB RAM 500GB HARD DISK 19 INCH MONITOR OPTICAL DRIVE 6 USB PORTS P/N: E2MQC-OPT Mfnr: HUNTER LAB
39	7352715	EA	Electrical measuring and testing equipment and accessories	GAUGE LEVEL TYPE: GITS VFG SERIES LIQUID LEVEL GAUGE WITH SIGHT GLASS VISIBLE LENGTH: 5-7/8 IN CONNECTION: SIZE: NPT 1/4 IN PRESSURE RATING: 120 PSI AT TEMPERATURE RANGE -40°F TO 250°F SECTIONS: LIQUID LEVEL COLUMN VIEW SIGHT GLASS WITH THE SCREW-TYPE VENTED CAP ON TOP LENGTH: 150 MM MATERIAL: ALUMINUM (GOLD ANODIZED) FINISH SIZE: A: 4 1/2 IN / B: 1 IN / C: 5 7/8 IN D: 5/8 IN. FFT: GITS 15316 STYLE VFG LIQUID LEVEL GAUGE 1/4-18 MALE NPT 5/8 OVERALL HEIGHT 5-7/8 BOTTLE HEIGHT LIQUID LEVEL COLUMN VIEW GAUGES ARE OF STUDY ONE-PIECE ALUMINUM CONSTRUCTION THE SIGHT WINDOWS ARE CUT FULL LENGTH TO PROVIDE EASY VIEWING OF A WIDE RANGE OF LIQUID LEVELS THE SCREW-TYPE VENTED CAP IS KNURLED FOR EASY REMOVAL BY HAND TO PERMIT CLEANING OF THE INSIDE OF THE GLASS SIGHT GLASS IS SECURELY LOCKED BETWEEN TWO HEAVY GASKETS THE BODY HAS A GOLD ANODIZED FINISH. USED IN D-END & N-END SIDS OF BPM-02315 MOTOR. GITS VFG SERIES LEVEL GAUGE WITH SIGHT GLASS; P/N: 15316 Mfnr: GITS MFG. CO. LLC
40	832183	ST	ELEMENT, HEATER	ELEMENT, HEATER; TYPE: ROUND, SIZE: DIA 12.5 X LG 8000 MM, ELECTRICAL RATING: 660 V, WATTAGE: 10203 W, MATERIAL: INCOLOY 80, TEMPERATURE: 500 °C; P/N: 0612120172, Mfnr: KLOPPER-THERM GMBH & CO. KG, P/N: V76693, SUPPL: LINDE LE; Mfnr DRG: 2.01-2.06_DRAWING, POS: 5; Mfnr DRG: 2.01-2.06_PARTLIST, POS: 5; TEST CERTIFICATE COMMENTS: REQUIRE TEST CERTIFICATE FOR EACH ELEMENT FOR HIGH VOLTAGE, IR AND ELEMENT COOL RESISTANCE TEST AS PER RELEVANT IEC/IEEE
41	1219036	EA	SENSOR	SENSOR: TYPE BROMINE MOUNT PLUG-IN, FFT: FOR DM-700-BR2, Mfnr: DETCON INC. Mfnr PART NO: 377-747501-015
42	1593748	EA	CABLE	CABLE: TYPE SENSOR VP 6, SIZE 17.5 MM AND LENGTH 3 M, MATERIAL CABLE MATERIAL COATING PVC, POTENTIAL 24 V DC, APPLICATION PH ANALYZER, Mfnr: HAMILTON Mfnr PART NO: 355109, TAG/EQUIP NO: 02-10-AT-3025 Mfnr: HAMILTON
43	1600311	EA	DETECTOR, RESISTANCE TEMPERATURE	DETECTOR, RESISTANCE TEMPERATURE: TYPE MINERAL INSULATED, RESISTANCE 100 OHM, TEMPERATURE RATING 0-600 °C, SHEATH MATERIAL SS 316, WIRE 3 DUPLEX, HEAD EXPLOSION PROOF GR II A, II B, STEM SIZE U-LG 245 200 MM + 45 MM (THREAD) MM, PROCESS CONNECTION NIPPLE 1/2 IN NPT X 100 MM X SS 304 (SPRING LOADED), SHEATH DIAMETER 6 MM, Mfnr: PHOENIX TEMPERATURE & ELECTROMECH. CO. W.L.L. Mfnr PART NO: UNK, SPECIFICATION SF20-34-15-005 REV: 0 ITEM NO: 2-TE609
44	1616229	ASV	MOTOR, SERVO	MOTOR, SERVO: ELECTRICAL RATING 19 MA, APPLICATION CONTROL VALVE - OIL SIDE ACTUATOR, FFT: RSE 200, Mfnr: K.K.K. Mfnr PART NO: UNK, DRAWING 2102863 REV: 0, TEST CERTIFICATE COMMENTS: OEM CONFIRMANCE CERTIFICATE REQUIRED
45	750916	EA	RELAY	RELAY: TYPE IRC, CONTACT RATING 250VAC 5A, CONTACT ARRANGEMENT NO/NC, ACTION DPDT, COIL VOLTAGE 115 VAC, MOUNT BASE MOUNT, ENCLOSURE IP40, FFT: J65A/19 (4500482937/29), OEM: UNITECH ENGINEERING SERVICES OEM PART NO: C12-A21X, For Tag/Equip No: INTERFACE PANEL

46	1034664	ST	MONITOR	MONITOR; TYPE: TOUCH SCREEN; RANGE: 0 TO 50 DEG C; POWER SOURCE: 24 V DC; SIZE: 19 IN; P/N: 64V6644-0A0C1-2A1, MFR: SIMATIC
47	984731	EA	ACTUATOR, PNEUMATIC	ACTUATOR, PNEUMATIC; TYPE: SINGLE ACTING, TRAVEL ROTATION 90 DEG, PRESSURE RATING 5-10 BAR, OPERATED OPEN, FFT: FOR ON/OFF VALVE; MOUNTING POSITION: TOP; SIZE: 360 MM; AIR FAILURE: OPEN, Mfr: ADLER, ITALY Mfr Part No: APR125SA, TEST & CALIBRATION CERTIFICATE IS REQUIRED
48	220198	ST	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC; TYPE: PRESSURE, INLET PRESSURE 3600 PSIG, OUTLET PRESSURE 0-250 PSIG, CONNECTION FNPT 1/4 IN, BODY MATERIAL SS, FFT: FOR CALIBRATION MIXTURE OF GASES; WITH PRESSURE GAUGES G058516 / G058511; TYPE OF FITTING: CGA350-55; PANEL/HP BOTTLE MOUNT, Mfr: GO INC. USA Mfr Part No: C1-1F11A3113501, DRAWING: 1041-40-501 Rev. 0, SPR: 241 Rev. 0 Item: 383, MODEL/MACHINE NO: C121
49	1604398	EA	FAN	FAN; TYPE: COOLING RADIAL, SIZE 300 MM, SPEED 150 RPM, ELECTRICAL RATING 230 V AC, MOUNT PANEL, CLASSIFICATION GROUP 1, ENCLOSURE RATING IP55, MATERIAL PLASTIC, NUMBER OF BLADES 3, DIRECTION CLOCKWISE, FFT-FOR VARIABLE SPEED DRIVE, MFR: WEG S.A. MFR PART NO: 12969971, SUPPL: BUSINESS TRIBUNE CO LTD, SUPPL PART NO: UNKNOWN
50	424655	ST	TRANSMITTER, FLOW	TRANSMITTER, FLOW; ELECTRICAL RATING 90-240 VAC, ELECTRICAL CONNECTION CAPTIVE SCREW, APPLICATION ULTRASONIC-1 CHANNEL, CLASSIFICATION EEXD IIC T5, MOUNT BRACKET, STANDARD CE, FFT-SIZE: 208 X 168; TEMP RANGE -20 TO 60 DEG C, SPECIAL (S = TROPICALISATION OF ELECTRONICS), MFR: PANAMETRICS INC MFR PART NO: XMT8681-11-00-0011-5, EQUIP SERIAL NO: 2344, MODEL/MACHINE NO: XMT8681
51	942879	ASY	ASSEMBLY	ASSEMBLY; TYPE: HYDRAULIC END, APPLICATION HP SCRUBBER PUMP, Mfr: PERONI POMPE SPA, ITALY Mfr Part No: UNK, DRAWING: 313H N2 000 ND1 SF2 Rev. 0 Item: 101-140, Model/Machine No: 3130N (S 70 X 95), Reference No: COD_313H N2 000 F02 (2)
52	1205809	EA	MODULE	MODULE; TYPE: (16) NON-COMMONED ROT TERMINAL PANEL, INPUT: 24 V DC, OUTPUT: 24 V DC, POWER SOURCE: 24 V DC, APPLICATION: SAFETY INSTRUMENTED SYSTEM (SIS); FFT: POT. FREE; P/N: 9668-110, OEM: INVENSYS
53	107594	ST	DIAPHRAGM, ACTUATOR	DIAPHRAGM, ACTUATOR; MATERIAL CMN-022, FFT-CONT VOLTAGE: MOD-3025 SERIES TYPE P 460NOTE: SHELF LIFE IS REQUIRED AND MSDS (MATERIAL SAFETY DATA SHEET) REQUIRED, IF APPLICABLE, OEM: GULDE FISHER OEM PART NO: GFD0935F012.3025, DRAWING: 9530.4 REV: 0
54	1066313	EA	METER, FLOW	METER, FLOW; TYPE: FLARE GAS, CONNECTION: FLANGED, RANGE: 0-1500 PSI G, MATERIAL: MONEL/HASTELLOY/ALLOY, STANDARD: CE; FFT: MAIN CONTROLLER UNIT; P/N: GF-868-1-11-20A14, MFR: PANAMETRICS INC, EQUIP MODEL NO: FLOWMETER PACKAGE FOR UTILITY FLARE; MFR DRG: 268-658, REV: A, POS: 1
55	1242878	ASY	ASSEMBLY	ASSEMBLY; TYPE: LONG CROSS BAR, APPLICATION FLIM WRAPPER, MFR: ARPA MFR PART NO: 299493, MFR DRG FLU-TE-AR-022-SPRM-044 REV: UNK ITEM NO: UNK, EQUIP SERIAL NO: 125-36 ASIW-35 LH MFR: UNKNOWN, EQUIP MODEL NO: 125-36 ASIW-35 RH MFR: UNKNOWN, EQUIP SERIAL NO: 13801 MFR: UNKNOWN, EQUIP SERIAL NO: 13802 MFR: UNKNOWN, EQUIP SERIAL NO: 13803 MFR: UNKNOWN, TAG/EQUIP NO: RS-FW-100 MFR: UNKNOWN, TAG/EQUIP NO: RS-FW-150 MFR: UNKNOWN, TAG/EQUIP NO: RS-FW-200 MFR: UNKNOWN
56	7363437	EA	System Cards	CARD ELECTRONIC TYPE: CONTROL BOARD FUNCTION: ICE MACHINE CONTROL BOX POTENTIAL: 120/240VAC 60MA MAX 50/60HZ P/N: 2511303 MFR: MANITOWOC ICE MODEL: J&Q SERIES MFR: MANITOWOC ICE SERIAL: 76-2782-3 MFR: MANITOWOC ICE
57	7315833	EA	BALLAST	BALLAST; TYPE: MAGNETIC VOLTAGE 120 V AMPERAGE 1.16 A WATTAGE 133 W LAMP 2 MFR: PHILIPS ADVANCE MFR PART NO: RC-2585-TP
58	7360973	EA	Weight measuring instruments	SCALE WEIGH TYPE: PLATFORM CAPACITY: 300 KG SPECIAL FEATURES: RUGGED CONSTRUCTION SUITABLE FOR INDUSTRIAL ENVIRONMENT AUTO SLEEP/POWER DOWN FUNCTION TO SAVE BATTERY LIFE FFT: 20 MM RED LED DISPLAY STABILIZATION INDICATION SELECTABLE UNIT OF CONVERSION ANTI-SLIP ADJUSTABLE LEVELING FEET ENVIRONMENTALLY PROTECTED LOAD CELL- IP65 AIRCRAFT GRADE HIGH TENSILE ALUMINUM LOAD CELL EQUIPPED WITH OVERLOAD PROTECTORS STAINLESS STEEL WEIGHING PAN LOW BATTERY INDICATION BUILT-IN BATTERY BACKUP P/N: PLT-300-M-T6 MFR: EAGLE
59	7120448	SE	FLOAT	FLOAT; TYPE: COLUMN DENSITY MEASUREMENT FFT: DENSITY RANGE: 0.9140 TO 0.9300 G/CM3 SET CONSISTS OF 5 FLOATS FOR EACH SET 0.9140 0.9180 0.9220 0.9260 AND 0.9300 GM/CC Mfr: NAIZAK GLOBAL ENGINEERING SYSTEM Mfr Part No: UNK
60	912639	ST	ELECTRODE	ELECTRODE; TYPE: GOUGING, APPLICATION PLASMA CUTTING MACHINE, Mfr: HYPERTHERM Mfr Part No: 220037, Suppl: ALRUGEE GROUP Suppl P/N: 220037, Model/Machine No: 1650
61	919064	EA	BOARD, PRINTED CIRCUIT	BOARD, PRINTED CIRCUIT; TYPE: MAIN; FFT: OPTIDIST PAC, SAPRES FOR PAC OPTIDIST AUTO DISTILLATION UNIT; P/N: 2101-340-001, MFR: PAC TEC
62	1612591	EA	RESTRICTOR	RESTRICTOR; TYPE: ORIFICE, APPLICATION: FLOW RESTRICT; FFT: FOR ORIFICE SIZE: 1/2IN; MATERIAL: SS 316; THK: 0.25IN; DIA: 3.5MM; FLUID/STATE: SERVICE WATER/ LIQUID FLOW: 10L/MIN; PRESSURE: 450KPA; TEMPERATURE: AMBIENT; SPECIFIC GRAVITY: 0.99; MOLECULAR MAS: 18; VISCOSITY: 0.55 CP; MAXIMUM DESIGN PRESSURE/ TEMPERATURE: 1300KPA/ 82 DEG C; P/N: OPP-5316-2-0150-0-5, MFR: USA INDUSTRIES, INC
63	1063943	EA	TRANSMITTER, FLOW	TRANSMITTER, FLOW; TYPE: CORIOLIS MVD AND DENSITY, RANGE 0-200 KG/HR, OUTPUT 4 - 20 MA, ELECTRICAL RATING 85-265VAC; 18-100VDC, STANDARD CSA, FFT-SELF SWITCHING; FLOW DIRECTION: FORWARD, MFR: MICRO MOTION INC. MFR PART NO: 2700C128BAEZZ, TAG/EQUIP NO: 36-FT-6553
64	709342	EA	DRIVE, VARIABLE SPEED	DRIVE, VARIABLE SPEED; POWER RATING 7.5 KW, POWER SOURCE 380-500 VAC, FFT: MOVITRAC, 14.4AMPS 3PHASE 50-60HZ +/-5%; INVERTER 08285268; SIZE 25; STD VERSION, IP 20;AMB TEMP MAX 50 DEGREES C; MIN 0 DEGREES C; SPEED RANGE 0-5500 RPM; FOR DP2 - PACKAGING AREA UNIT 230, Mfr: SEW-EURODRIVE Mfr Part No: MC07B0075-5A3-4-00, DRAWING: DPL-13004Z-4A Rev: UNK Item: 1.3, For Tag/Equip No: 2Y-3132-A-V4
65	681363	FT	CHAIN, POWER TRANSMISSION	CHAIN, POWER TRANSMISSION; STYLE SIMPLEX, PITCH 3/4 IN, TYPE ROLLER, MATERIAL STEEL, LENGTH 10 FT, APPLICATION ROTARY FEEDER, FFT-FOR BUHLER MIAG DIAMOND 60' COTTERED CHAIN PACKAGING, MFR: DIAMOND MFR PART NO: 60 STANDARD SERIES, COTTERED TYPE, MODEL/MACHINE NO: CHEM 45/60, SERIAL NO: 60298 SELF LUBRICATED
66	984483	EA	MODULE	MODULE; TYPE (16) CHANNEL ETA ANALOG INPUT, APPLICATION PCIMS/PSS SYSTEM/F AND GDS, Mfr: TRICONEX Mfr Part No: 9771-20X
67	1647317	EA	MOTOR, ELECTRIC	MOTOR, ELECTRIC; POWER RATING: 1 HP, ELECTRICAL RATING: 460V, 60HZ, 2.4A, SPEED: 1100 RPM, FRAME: 48B, MOUNT: VERTICAL SHAFT UP, ENCLOSURE: SEMI, INSULATION CLASS: B, PHASE: 1 PH, P/N: 024-27665-000, OEM: A. O. SMITH CORPORATION, MODEL: F48J10A50, SERIAL: 025070M1, DRAWING: 025-18241-000, POS: 5, TEST CERTIFICATE COMMENTS: WARBENTY CERTIFICATE
68	1621076	EA	FAN	FAN; TYPE: HEATSINK COOLING, SIZE DIA 183 MM, ELECTRICAL RATING 230V; 50/60 H; 197W, MOUNT DIRECT, MATERIAL CS, MFR: KTRUBO MFR PART NO: GD133-2K, DRAWING 120000-EW044001-V100831 REV: 0 ITEM NO: PAGE2
69	7337310	EA	Electrical bushing	BUSHING ELECTRICAL CONDUCTOR TYPE: INSULATOR VOLTAGE: 15 KVAC AMPERAGE: 233 A AC LENGTH: 6 IN FFT: INDOOR DIA: 3/4 FOR ABB MAKE 4700 KW 13.2 KV MOTOR. SR. NO: HM1006849 TYPE: ABM 630 L2L BSN B. P/N: 6600-510 4X2 RED MFR: MAR-BAL INCORPORATED MFR DRG: UL E84767 MFR: MAR-BAL INCORPORATED TEST CERTIFICATE COMMENTS: FACTORY TEST CERTIFICATE
70	7356287	EA	Viewing and observing instruments and accessories	MICROSCOPE RANGE: 10-200X ZOOM COMMERCIAL SIZE: VERTICAL HEIGHT 400 MM HORIZONTAL DISTANCE 770 MM BASE SIZE 98 X 80 X 116 MM MAX CLAMP 50 MM TYPE: UNIVERSAL ROTABLE ARTICULATING CLAMP ARM STAND FFT: MANUFACTURER LAPSUM MODEL: LS-DV1137F MFR: LAPSUM
71	1613531	EA	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC; TYPE: PRESSURE REDUCING, INLET PRESSURE 250 PSI, OUTLET PRESSURE 0-125 PSI, CONNECTION NPT 1/2 IN, BODY SIZE 2.57 IN, BODY MATERIAL ZINC, OPERATING TEMPERATURE 150 °F, FFT-MAX FLOW 9.3 CFM; FILTER MESH: 5 MICRON; SERVICE AIR, MFR: WILKERSON CORPORATION MFR PART NO: B18-04-FL-00
72	1199302	ST	REGULATOR, PRESSURE	REGULATOR, PRESSURE; INLET PRESSURE 1500 PSIG, OUTLET PRESSURE 1500 PSIG, CONNECTION SIZE 3/4 IN, CONNECTION TYPE NPT, BODY MATERIAL 123-1+6+S CS/CS/5405, TYPE REPAIR, FFT-INLET TEMP 1500/400DEG F, MFR: CASICO INC MFR PART NO: 955-5457-45X29393C, SERIAL NO: AC3459-002-07
73	1596518	EA	RELAY	RELAY; COIL VOLTAGE 115 V AC, ACTION 1NC, CONTACT RATING INDUCTIVE AC-15, 4 A/230 V; INDUCTIVE DC-13, 2 A/24 V; TYPE SAFETY MONITORING, CONTACT ARRANGEMENT 2 N/O, MOUNT PANEL MOUNTED, ENCLOSURE IP 20, TERMINAL SCREW, STANDARD EN60439-1, EN60947-1/5/7, EN61000-6, EN62061, EN ISO 13849-1, CONTACT MATERIAL COPPER, OEM: STI OEM PART NO: SR101A02
74	897485	EA	CIRCUIT	CIRCUIT; TYPE: OPTICS SUPPLY, APPLICATION: MASS SPECTROMETER P/N: 816096, MFR: EXTRELS CMS
75	42846	EA	TRANSMITTER	TRANSMITTER; TYPE: ELECTRONICS ASSY, FFT-WITH UNIVERSAL MOUNTING KIT- 3-8050; OLD PART NO: 3-8550-1, MFR: GEORGE FISCHER SIGNET MFR PART NO: 3-9900-1P + 3-8050
76	1596116	ASY	SWITCH, LIMIT	SWITCH, LIMIT; CONTACT RATING 20A AT 125-250 VAC; 0.5A AT 125VDC, TYPE INDICATOR, CLASSIFICATION ATX II 2 G EX DIB T4-TE, II 2 D EX D2 A21, ACTION 2 SPDT, CONTACT ARRANGEMENT 2NO-2NC, ENCLOSURE IP67, APPLICATION ACTUATOR, FFT-ASSEMBLY CONSISTS OF LIMIT SWITCH AND MOUNTING KIT P/N:F09475-524; VISUAL DISPLAY-STD 90 DEG, GREEN(OPEN), RED(CLOSE); CONDUIT ENTRY: 2(3/4 IN NPT), MFR: TOPWORX MFR PART NO: DXP-M21GSEB, REFERENCE NO: D SERIES
77	1242861	FT	CHAIN, POWER TRANSMISSION	CHAIN, POWER TRANSMISSION; PITCH 5/8 IN, TYPE ROLLER, MATERIAL SS, LENGTH 10 FT, WIDTH 3/8 IN, DIAMETER 0.579 IN, LOAD CAPACITY 4991 LBS, APPLICATION SEAL FRAME AND DRIVE ASSEMBLY, FFT, MFR: PEER MFR PART NO: RC50, MFR DRG 292362 REV: A ITEM NO: 26
78	1607552	EA	BOARD, INSULATION	BOARD, INSULATION; SIZE LG 1000 X WD 600 X THK 50 MM, MATERIAL SUPERWOOL PLUS FIBRES, MINERAL FIBRES AND ORGANIC BINDER, FFT-SUPERWOOL PLUS BLOK 1100; TEMPERATURE 1100 DEG C; MFG: MORGAN, USED FOR FURNACE INSULATION; MTC REQUIRED ALONG WITH MATERIAL SUPPLY, MFR: MORGAN ADVANCED MATERIALS MFR PART NO: UNK, MFR DRG 126-1289,1290,1297,1299,1300 REV: 3, 3.3, 3.4 ITEM NO: E3, INSPECTION REQUIREMENT: NON HAZARDOUS MATERIAL, TEST CERTIFICATE COMMENTS: MTC MUST BE PROVIDED UPON DELIVERY
79	188392	ST	SWITCH, LIMIT	SWITCH, LIMIT; CONTACT RATING: 53 A, ACTION: ON/OFF, CONTACT ARRANGEMENT: NO/NC, ENCLOSURE: IP66; FFT: TYPE: BOX IAR / 2575; FOR DOUBLE BRIDGE ELECTRIC BRIDGE CRANE MODEL - DGB, 21-2X-401; MATERIAL STEEL; P/N: AP104, MFR: TALKRANE; DRAWING: APP/1, POS: 4
80	1003232	EA	LOAD CELL	CELL, LOAD; CAPACITY 2 TON, FFT: FOR WEIGHING MACHINE, Mfr: METTLER TOLEDO INTERNATIONAL INC Mfr Part No: SB-2
81	102783	ST1	ASSEMBLY	ASSEMBLY; TYPE COUPLING, APPLICATION GEAR SET, FFT: WITH FINISHED BORE, KEY WAY, HUB-11-SLEEVE-REAMER BOLT, NUT AND SPRING WASHER; TYPE: MTSSA150 PRID FAN CLUTCH, Mfr: DENGYOSHA MACHINE WORKS Mfr Part No: AIR-410B, Drawing 3GA0480-1Y01 Rev: 0 Item No: POS 1 TO 10, Drawing PK26492/A3 Rev: 0 Item No: POS 1 TO 10
82	1039258	EA	DETECTOR, LEAK INSTRUMENT	DETECTOR, LEAK INSTRUMENT; TYPE: GAS DETECTION, RANGE 0-200 PPM, FFT-ULTRARAE 3000 MODEL PGM-7360 INCLUDES; MONITOR, DATALOGGING WITH PRORAE STUDIO, TRAVEL DOWNLOAD CHARGER, RAE UV-LAMP AND RAE-SDEP TUBES, AS SPECIFIED, FLEX-IPROBE AND SHORT PROBE, EXTERNAL FILTER, RED RUBBER BOOT, ALKALINE BATTERY ADAPTER, LAMP CLEANING AND TOOL KIT, LI-ION BATTERY WITH UNIVERSAL AC/DC ADAPTER AND INTERNATIONAL PLUG KIT, IF SPECIFIED, RESOURCES CD-ROM AND MAINTENANCE MANUAL, SOFT LEATHER CARRYING CASE. ACCESSORIES KIT INCLUDES; HARD TRANSPORT CASE WITH PRE-CUT FOAM, 5 POROUS METAL FILTERS AND O-RING, GAS OUTLET PORT ADAPTER AND TUBING, ORGANIC VAPOR ZEROING KIT, CALIBRATION KIT INCLUDES: 3/4L CYLINDER CALIBRATION GAS, AS SPECIFIED, REGULATOR AND FLOW CONTROLLER, MFR: MAGUS INTERNATIONAL MFR PART NO: 059-0310-200, MFR: RAE SYSTEMS MFR PART NO: 059-0310-200, MODEL/MACHINE NO: PGM-7360
83	269239	EA	BRAKE	BRAKE; TYPE ELECTRO MAGNETIC, APPLICATION MOTOR, FFT-COMLETE FOR SEW MOTORS 1.1/2.2/3KW, SUITABLE FOR MOTOR TYPE KAB60100LABMG/VS, KAB7D100LABMG/VS, FA67D9054BMG, SA47D9054BMG & K77D9054BMG, USED IN BAGGING LINES#B/C/D/E/F, SIZE 120V/20MM, TYPE/MODEL 120-3LEADS, MFR: SEW EURODRIVE MFR PART NO: UNKNOWN
84	984227	EA	ACTUATOR, PNEUMATIC	ACTUATOR, PNEUMATIC; TYPE: SINGLE ACTING, PRESSURE RATING: MAX 150 PSI G, OPERATED: SPRING RETURN/CLOSE; FFT: SIZE: 160; VALVE TO FAIL CLOSE AT LOSS OF AIR SUPPLY; FOR ON/OFF VALVE; HAND WHEEL: 522 MM; MOUNTING POSITION : TOP; P/N: SR160-6-2, MFR: VALBIA, MODEL: 825R0079, MFR: VALBIA
85	928496	EA	KIT, TERMINATION	KIT, TERMINATION; TYPE END, FFT: CONSISTS OF: RUBBER END CAP, RTV ADHESIVE AND CAUTION LABEL, Mfr: THERMON MANUFACTURING COMPANY Mfr Part No: 23666, Mfr: THERMON MANUFACTURING COMPANY Mfr Part No: UNKNOWN, Mfr DRG VD-1910-1273-0004 Rev: 0 Item No: UNK
86	488840	EA	MOTOR, GEARED	MOTOR, GEARED; POWER RATING: 1.5 KW, ELECTRICAL RATING: 266/460VAC 5.30/3.20A 60HZ, PHASE: 3, OUTPUT SPEED: 1410/131 RPM, RATIO: 20.3:1, GEARBOX TYPE: SA57, MOUNT: B8, ENCLOSURE: IP55; FFT: TYPE SA57/D190U4/BMG / E55; FOR GEAR BRIDGE OF LAYER FEEDER, POS NO: P#50 M1, 3" IEC 34, I: 20.33:11.99 NM, 0.78 PF, IM: M1A, 50 DEG, 42.97 KW, IP: 55, INSUL CL: F, BRAKE: 266 VAC, 20 MM, STANDARD, IEC 34, P/N: SA57/ D190U4/B2/E5757AL, MFR: SEW EURODRIVE, P/N: SA57/D190U4/BMG/E55, MFR: SEW EURODRIVE, SERIAL: 01.308019120.0002304, MFR: SEW EURODRIVE, EQUIP SERIAL NO: 17891, MFR: MOLLERS; DPL-DPL-75000Z-4C, POS: POS 1
87	705707	EA	THERMOCOUPLE	THERMOCOUPLE; TYPE DUAL ELEMENT, FFT-DATA HAS BEEN CHANGED TO MATCH DS-210-J02.01.060 WITH SPEC NO. 2J-016 (CHANGE MADE BY SULAIMAN ALMOWALED 5530), MFR: SANDELIUS MFR PART NO: S14-250K316-RS-19-465-516R, TEST CERTIFICATE COMMENTS: RELATED MILL CERTIFICATE TO BE SUBMITTED WITH THE ORDER
88	488420	EA	DETECTOR	DETECTOR; TYPE: COMBUSTABLE GAS; FFT: KIT CONSIST: 3/4" RTD COMBUSTIBLE HEAD (P/N: 7001-315-TE) + BOARD (P/N: 7001-368-TE); FOR OXYGEN ANALYZER SYSTEM (THERMOX); FOR EQUIP NO: 14-AT-1483A-H; P/N: 7001-368-TE, MFR: IMTECH SYSTEMS BV
89	167217	EA	SWITCH	SWITCH; TYPE TORQUE, APPLICATION ELECTRIC VALVE ACTUATOR, FFT: FOR MODELS: L120-10/20/40/85/190, MAT: PLASTIC/STEEL BULLETIN: L120-11000 ITEM 300, Mfr: LIMITORQUE CORPORATION Mfr Part No: 21800-099

137	794975	EA	MOTOR, GEARED	MOTOR, GEARED	MOTOR, GEARED; POWER RATING: 3.7 KW, ELECTRICAL RATING: 380-500 VAC, 4.09 A, 60 HZ, PHASE: 3 PH, OUTPUT SPEED: 135 RPM, RATIO: 12.48, GEARBOX TYPE: KA67, SHAFT: DIA 40 MM, CLASSIFICATION: NON HAZARDOUS, MOUNT: M1/B, INSULATION CLASS: H, ENCLOSURE: IP65, TYPE: SQUIRREL CAGE INDUCTION; FFT: FOR NEW LAYER STACKING TABLE IN DR1 - UNIT 30; TECH POS 13050-1; BRAKE VOLTAGE: 230 V; BRAKE TORQUE: 40 NM, AMBIENT TEMPERATURE: 50 DEG C, BMG2; P/N: KA67 DRN100L4/MM40/M0/AVSK/TFO/AVSK/TF, MNFR: SEW EURODRIVE, REFERENCE: ART# 38036; TEST CERTIFICATE COMMENTS: MNFR TEST CERTIFICATE
138	765359	ST	MODULE	MODULE	MODULE: TYPE: SWITCH, CATALYST, APPLICATION: DIESEL GEN NETWORK SWITCHES PANELS; FFT: OLD PART NO.: WS-C2950-24E1, 2950 SERIES INTELLIGENT; SWITCH 24 1Q/100 PORTS, 2 1000BASE X PORTS, EI INSTALLED, SUPPLY RATING: 100-127V, 1A TO 200-240V, 0.5A, FREQUENCY: 50/60HZ, TYPICAL S/N: FOC102WVNY, CNM9FOOCR, IOS VERNISON, 12.1.9.2.1 EAG, 0016C7C04640, PROVISION FOR: D.C. INPUT FOR REMOT POWER SUPPLY RATING: +12V 4.5A; COLD MILL COLOUR COATING LINE; P/N: WS-C2960-24TC-L, OEM: CISCO SYSTEMS
139	526663	EA	MOTOR, GEARED	MOTOR, GEARED	MOTOR, GEARED; POWER RATING: 0.37 KW, ELECTRICAL RATING: 460 VAC, 1.07 A, 60 HZ, PHASE: THREE, OUTPUT SPEED: 93 RPM, RATIO: 1680:93, GEARBOX TYPE: HELICAL PARALLEL, MOUNT: FOOT, TYPE: BRAKE; FFT: BRAKE VOLTS=266; BRAKE NM=5 WITH CURRENT RELAY-SR11 USED FOR LINE# 6; FOIL MACHINE FILM TRANSPORT; NOTE: DO NOT SUBSTITUTE, TO BE PURCHASED THROUGH MOLLERS/GOLDEN WING FOR COMPATIBILITY OF THIS MOTOR WITH THE PACKAGING MACHINES INSTALLED IN KEMVA MANUFACTURED BY MOLLERS; P/N: R27 DRN71M4/B605/2 (REPLACEMENT), MNFR: SEW EURODRIVE, P/N: R27D71D4/BMG/2 (OLD), MNFR: SEW EURODRIVE
140	1052170	EA	LAMP	LAMP	LAMP: TYPE PANEL, WATTAGE 1.2 W, VOLTAGE 30 V, BASE BASS, COLOR CLEAR, FFT: CURRENT: 40 MA; LIFE: 2000 HOURS; COLOUR RENDERING INDEX (CRI): 100; DIMMABLE; DIMENSIONS: HT 23 X DIA 9 MM; APPLICATION LOCAL PANEL INDICATION; REFERENCE NO. 8T23/30/1.2 OR EQUAL,
141	717819	FT	CABLE, ELECTRICAL	CABLE, ELECTRICAL	CABLE, CONTROL- CONDUCTOR 1 PAIR, CONDUCTOR RATING 22 AWG, STANDARD UL, TYPE FIRE RESISTANT, FFT: SHIELDED; IE108998, Mfr: BELDEN Mfr Part No: 8737, DRAWING: 011-91311125315 Rev: UNK
142	1603643	EA	THERMOCOUPLE	THERMOCOUPLE	THERMOCOUPLE; TYPE: K - DUPLEX, TEMPERATURE RANGE: 0-1000 °C, SHEATH MATERIAL: SS 310, HEAD: IP65 WEATHER PROOF, JUNCTION: DUAL ELEMENT, OVERALL LENGTH: 590.55 IN, DESIGN LENGTH: 472.44 IN; P/N: K316DU310-5T1/2-597-04(S), SP= 6 INCH LEAD, MNFR: THERMO ELECTRIC CO., INC., OEM: THERMO ELECTRIC CO., INC., REFERENCE: 5R017-778
143	928563	EA	MOTOR, GEARED	MOTOR, GEARED	MOTOR, GEARED; POWER RATING: 0.37 KW, ELECTRICAL RATING: 266/460 VAC, 1.59/0.91 A, 60 HZ, PHASE: 3 PH, OUTPUT SPEED: 1730/111 RPM, GEARBOX TYPE: HELICAL WORM GEAR, FFT: TORQUE: 29.5 NM; LAYER FEEDER LIP/DOWN: A/B/11/11/K/L/M LINE, BRAKE VOLTAGE: 266 VAC, RECTIFIER: BG3, COMM. NO.: 18100/18151; P/N: SA37DRN71M4/B605/DH, MNFR: SEW EURODRIVE, REFERENCE: 21711228, REFERENCE: 85051500 NEW; DRAWING: DPL-0891902-4A, POS: 1.1
144	885152	EA	RELAY	RELAY	RELAY: TYPE CHECK SYNCHRONISING, FFT: BUSBAR INPUT: 115V 0.5MA 50/60HZ; GEN INPUT: 115V <20MA 50/60HZ; SYN OUTPUT: 250V/24VDC 8A; FOR THE MAC AND BAC EXCITATION PANEL; PH-III PLANT, OEM: ABB OEM Part No: 3BMS003667-7, Mfr: DEIF Mfr Part No: UNK, Drawing 885152 Rev: F Item No: P2, Model/Machine No: CSQ-3 LAND Mfr: DEIF
145	749458	EA	COIL, ELECTRICAL	COIL, ELECTRICAL	COIL, ELECTRICAL: TYPE CONTACTOR, ELECTRICAL RATING 120V 60HZ, FFT: FOR PHASE-5 HEATER PANELS, COIL FOR CONTACTOR LC1-F30, MNFR: HEATEX LTD. Mfr Part No: 17223.01.AG21, DRAWING: 17223.01.03 Rev: 3 Item: KM2,KM3,KM4, Model/Machine No: LX1-F110, Reference No: P. O. NO. 2E6151, Tag/Equip No: 40-SG-505 A/B/C, Equip/Tag Serial No: 17223.01.01B
146	900953	EA	MOTOR, GEARED	MOTOR, GEARED	MOTOR, GEARED; POWER RATING: 1.5 KW, ELECTRICAL RATING: 380-500VAC 50HZ, PHASE 3, GEARBOX TYPE HELICAL WORM, CLASSIFICATION C I DIV 3 GR D, MOUNT VERTICAL FOOT/MAB, ENCLOSURE IP54, TYPE BRAKE, STANDARD CE, IEC, UL, Mfr: SEW-EURODRIVE Mfr Part No: SA67D90L4MM15/BW1 (OLD P/N), Mfr: SEW-EURODRIVE Mfr Part No: SA677 DR90M4/MM15, MANDRG: 08 409 05 94 Rev: 0, Serial No: 01.1168143101.0001.07, 01.1174974701.0001.07, Equip/Tag Model No: SA67D90L4MM15/BW1
147	1347851	EA	LEAD, TEST	LEAD, TEST	LEAD, TEST: CONNECTORS AC220 SUREGRIP ALLIGATOR CLIP SET; AC280 SUREGRIP HOOK, LENGTH 63 IN, MNFR: FLOUPE M TLK-225
148	1636288	EA	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC; TYPE: PRESSURE CONTROLLER, INLET PRESSURE: MAX 6000 PSI G, OUTLET PRESSURE: 0 - 250 PSI G, CONNECTION: FNPT 1/4 IN, BODY SIZE: DIA 54 X LG 102 MM, BODY MATERIAL: SS 316L; P/N: PR1A11A1J1313, MNFR: GO REGULATOR INC. USA., P/N: PR1A11A1E11313, MNFR: GO REGULATOR INC. USA., 50 38 0
149	904471	ST	SWITCH, PRESSURE	SWITCH, PRESSURE	SWITCH, PRESSURE: TYPE DIFFERENTIAL WITH INDICATOR, RANGE 0 - 4 KG/CM2, CONNECTION FNPT 1/4 IN, FFT: SETTING 2.5 KG/CM2; SERIAL NO. 43943; MAX. WP. P = 6000 PSI/40MPA, MODEL:120-SA-10-0 (EA) RATED CLASS I, DIV II, FOR SYNTHESIS GAS COMPRESSOR A-G8601 (103-1), Mfr: MID-WEST INSTRUMENTS Mfr Part No: UNK, Mfr: MITSUBISHI HEAVY INDUSTRIES, LTD. Mfr Part No: UNK, Model/Machine No: 120 Mfr: MID-WEST INSTRUMENTS
150	1667205	EA	INDICATOR	INDICATOR	INDICATOR; TYPE: MAGNETIC LEVEL, SIZE: 0-2300 MM, MATERIAL: SS ASTM A351 GR C8M, RANGE: 1896 TO 2414 KPA, SCALE: 2300 MM, MOUNT: VERTICAL FLANGE MOUNT, CONNECTION: 3/4 IN- 300 LB RF, DISPLAY TYPE: LOCAL GAUGE, APPLICATION: HIGH PRESSURE COMPRESSION CHAMBER; P/N: LG6C-3/4"-300H-SG-527C-2414KPA G-2300MM, MNFR: MAGTECH INDUSTRIES CORPORATION, SERIAL: 6428, MNFR: MAGTECH INDUSTRIES CORPORATION
151	901839	EA	RECTIFIER	RECTIFIER	RECTIFIER: TYPE BRAKE, VOLTAGE 230/500 VAC, INDUSTRY STANDARD BGE 1.5, STANDARD DIN, OEM: MASCHINENFABRIK BEUMER GMBH & CO KG OEM Part No: 10033, Mfr: SEW-EURODRIVE Mfr Part No: BGE 1.5, MANDRG: 2945, 5702, 2227 Rev: 0 Item: 6, 7.1
152	776747	EA	DETECTOR	DETECTOR	DETECTOR: TYPE OXYGEN GAS, FFT: 4-20MA OUTPUT WITH DIGITAL DISPLAY, 3 RELAY OUTPUTS, Mfr: DETCON INC. Mfr Part No: DM634, Suppl: ABB PROCESS ANALYTICS Suppl P/N: DM634
153	197998	ST	SENSOR	SENSOR	SENSOR: TYPE OXYGEN, ELECTRICAL CONNECTION (2) WIRE FORK TERMINALS, SIZE DIA 35 X LG 28 MM, MOUNT CLAMP, Mfr: RIKEN KEIKI CO LTD Mfr Part No: 4981-05, Drawing 1577E Rev: 0, SPR 2315 Rev: 0 Item No: 013, Model/Machine No: OS-811, Equip Model No: OX-621A, REQUIRED SHELF LIFE SHOULD BE 3 YEARS FROM DATE OF PRODUCTION
154	409384	EA	SWITCH, PRESSURE	SWITCH, PRESSURE	SWITCH, PRESSURE: FFT: PRESSOSTAT, Mfr: TRAFAG, SWITZERLAND Mfr Part No: TYPE 900,2673.801
155	1553958	EA	MOTOR, GEARED	MOTOR, GEARED	MOTOR, GEARED; POWER RATING 2.2 KW, ELECTRICAL RATING 266/460VAC 7.1/4.1A 60HZ, PHASE 3, OUTPUT SPEED 1710/63 RPM, RATIO 26.97:1, GEARBOX TYPE HELICAL, ENCLOSURE IP54, STANDARD IEC34, FFT: INCLINED CONVEYOR MOTOR-GEAR FOR PVC PACKAGING LINE-C, Mfr: SEW-EURODRIVE Mfr Part No: R570100M4/BMG, DRAWING: E23-3522 Rev: 0 Item: 1, Serial No: 01.3077026410.0001.08, Equip/Tag Model No: 03-VM-15415C
156	918112	EA	CABLE	CABLE	CABLE; TYPE: Coil, SIZE: 900 mm, MATERIAL: Copper; FFT: FOR TOP SEAM, APPLICATION: BAGGING MACHINE (WEIGHT: 25KG); P/N: 76060127, MNFR: WINDMOLLER & HOLSCHER KG
157	1592402	EA	CYLINDER, ACTUATING, LINEAR	CYLINDER, ACTUATING, LINEAR	CYLINDER, ACTUATING, LINEAR; TYPE: PNEUMATIC, SHORT STROKE, BORE: 40 MM, ACTUATION METHOD: PISTON, STROKE: 25 MM, WEIGHT: 10 BAR, CONNECTION TYPE: THREADED; FFT: COMPLETE WITH PNEUMATIC CYLINDER (35021936), ARTICULATION HEAD, BEF10K1.25(02227401), HEXAGON HEAD SCREW, M10X35 V4A (03282189), HEXAGON NUT, M10X1.25V4A (03283040), ANGLE (30103953), THREADED JOINT, HR.7010081(02822127), NIPPLE, RED, G1/8XG1/8(02822043), SEALING RING, 15-01 AL(02854820); P/N: S733503022, MNFR: NORGREEN LTD; TEST CERTIFICATE COMMENTS: TEST CERTIFICATE NEEDED
158	431633	EA	MOTOR, GEARED	MOTOR, GEARED	MOTOR, GEARED; POWER RATING 0.55 KW, ELECTRICAL RATING 220-380VAC 3.2/1.85A 60HZ, PHASE THREE, OUTPUT SPEED 261 RPM, RATIO 6.37:1, GEARBOX TYPE BEVEL, MOUNT M1A SHAFT, ENCLOSURE IP54, TYPE BRAKE, STANDARD CE, IEC 34, FFT: PALLETIZING LINE ROLLER CONVEYOR WITH TURNING GRATING, SHORT; MOTOR: SPEED = 1660RPM; INSULATION CLASS H; TORQUE = 20NM; BRAKE VOLTAGE = 220VAC, Mfr: MOELLER GMBH Mfr Part No: UNKNOWN, DRAWING: DP2-060202-4F Rev: 0, Reference No: KA37 D780K4/BMG Mfr: SEW-EURODRIVE, DP2-060202-4F
159	798223	EA	CYLINDER, ACTUATING, LINEAR	CYLINDER, ACTUATING, LINEAR	CYLINDER, ACTUATING LINEAR: TYPE PNEUMATIC, BORE 63 MM, STROKE 90 MM, FFT: Di=63 H=90/SPC, FOR DPI UNIT-30 PALLETIZERS; OLD P/N: 35006109, Mfr: BEUMER MASCHINENFABRIK GMBH Mfr Part No: 35021940
160	477534	EA	CAPACITOR	CAPACITOR	CAPACITOR: TYPE FIXED, CAPACITANCE 21 MICRO F, VOLTAGE 580 VAC, FFT: FOR LIGHTING FIXTURES TYPE 297F6946RC, Mfr: SAUDI LIGHTING COMPANY LTD Mfr Part No: A41021-21A, Suppl: SAUDI ELECTRIC SUPPLY COMPANY SUPP P/N: UNKNOWN
161	937754	ASY	PANEL, CONTROL	PANEL, CONTROL	PANEL, CONTROL: TYPE OPERATOR, APPLICATION BAGGING MACHINE, FFT: FOR SIMANTIC PANEL PC677; 15 INCH TOUCH; MAIN BOARD CV3 WITH PROFIBUS, CEL M370, 1.5GHZ, 400 MHZ; 1MB SLC; 512 MB DDR5; 533 SODIUM; 40 GB HDD SATA + DVD ROM; WINDOWS XP PROFESSIONAL, MUI SP2/677, Mfr: MASCHINENFABRIK MOLLERS GMBH Mfr Part No: 600695, Model/Machine No: 6AV7802-0BA10-1A00 Mfr: SIEMENS AG
162	798452	EA	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC; TYPE PRESSURE, CONNECTION 1/4 IN, FFT: TECH DATA 1/4" 535 140 220 0 W/OUT MANOMETER, FOR PALLETIZERS, OEM: BEUMER MASCHINENFABRIK GMBH OEM Part No: 02855006
163	523414	ST	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC: TYPE PRESSURE, FFT: FOR NEW BAGGING MACHINE-C SPECIFICATIONS : 535 132 420 0, MODEL# DIAMANT 1800-7331 & ZAKI-150, SERIAL#0514; M/N#5351320200; TAG#R-7101C; 98H-021V; L/DPE PHASE VII / L/DPE SPARE ITEMS, Mfr: WINDMOLLER & HOLSCHER KG Mfr Part No: 02855197, Mfr: REKROTH MECMAN Mfr Part No: 535.132.420.0
164	987149	M	CABLE, ELECTRICAL	CABLE, ELECTRICAL	CABLE, ELECTRICAL; TYPE: CONTROL, CONDUCTOR SIZE: WIRE 5 CORE, INSULATION: BAGGING LINES, APPLICATION: ALL LINES PC AND PROXIMITY SWITCH CABLE; P/N: A02 GW114659, MNFR: MOLLERS
165	1662595	EA	MOTOR, GEARED	MOTOR, GEARED	MOTOR, GEARED; POWER RATING: 480 V, ELECTRICAL RATING: 400 V, PHASE: 3, OUTPUT SPEED: 1680 RPM, RATIO: 0.29, GEARBOX TYPE: HELICAL WORM, MOUNT: M1, ENCLOSURE: IP 55, TYPE: HELICAL; FFT: PARALLEL SHAFT HELICAL; FOR STRECH HOOD SYSTEM; Mfr: P/N: 21683521, MNFR: GOLDEN WING, MODEL: 19850, DRAWING: 27013282-4A, POS: 1.1
166	273766	ST1	CONNECTOR, ELECTRICAL	CONNECTOR, ELECTRICAL	CONNECTOR, ELECTRICAL: TYPE WIRE, FFT: FOR TOP SEALING BAG M/C SEALING CURRENT, TYPE #WAVE 13/919, TAG#W-7101D; C#06 MAR.96, Mfr: WINDMOLLER & HOLSCHER KG Mfr Part No: 04 502 089
167	937808	EA	ASSEMBLY	ASSEMBLY	ASSEMBLY: TYPE TAKE UP, FFT: ASSEMBLY 2, Mfr: MESUTRONIC GERMANY Mfr Part No: 300619, MANDRG: 96000.00.51, ED X Rev: 01, 51.010998.01(SPARE PART LIST) Rev: 01, Serial No: 020705-T
168	882881	EA	SWITCH, PROXIMITY	SWITCH, PROXIMITY	SWITCH, PROXIMITY: TYPE SENSOR, SENSING RANGE 8 MM, CONTACT RATING 10-30V 0-200MA 0-500HZ, CONNECTION PLUG IN, STANDARD EX II 3D; CE, IEC/EN 60947-5-2:2004, ACTION PNP, FFT: M18 X 1 X HT 70MM, FOR PALLETIZERS, Mfr: MOLLERS, Mfr Part No: 112017, Model/Machine No: NBB8-18GM60-A2-V1 Mfr: PEPPERL & FUCHS GMBH
169	1546232	EA	MOTOR, BRAKE	MOTOR, BRAKE	MOTOR, BRAKE: POWER RATING 0.55KW/51, SPEED 87 RPM, FRAME D780K, ELECTRICAL RATING 266/400 V AC, 1.53A,60HZ, 1660RPM, 0.72PF, STANDARD IEC 60034, FFT:HELICAL-WORM GEARED; FOR NMS065-9; P.O.NO: N8-M3-PO-90-22015P, SUPPL: MASCHINENFABRIK MOLLERS GMBH SUPPL PART NO: UNKNOWN, DRAWING DPL-1631021-4B Rev: 0 Item No: POS 1.1
170	1593272	ST	HEATER	HEATER	HEATER: TYPE: HEATING CABLE, RATING: 230V 4KW, APPLICATION: PACKAGING; P/N: HOTROD, MNFR: HOTSET, P/N: 35060809, SUPPL: WINDMOLLER & HOLSCHER KG, P/N: 9006898, SUPPL: BEUMER MASCHINENFABRIK GMBH
171	705162	EA	RELAY	RELAY	RELAY; COIL VOLTAGE: 24 V DC, ACTION: (1) SPDT, CONTACT RATING: 1 A AT 28.8 VDC, TYPE: COMPACT, CONTACT ARRANGEMENT: NO NC, MOUNT: DIN RAIL, ENCLOSURE: NEMA, TERMINAL: 5; FFT: RE 3-4-001/2/G; P/N: 04420684, MNFR: WINDMOLLER & HOLSCHER KG, DRAWING: 1, POS: 001
172	554640	EA	MOTOR, BRAKE	MOTOR, BRAKE	MOTOR, BRAKE; POWER RATING: 1.5 KW, SPEED: NORMAL, ELECTRICAL RATING: 460 V; FFT: HELICAL-WORM GEARED; FOR N90M61; P.O.NO: N8-M3-PO-90-22015P PART NUMBER CHANGED TO SP004090; DRAWING: DTF-202012-4E POS 1.1
173	932120	EA	SWITCH, PUSH	SWITCH, PUSH	SWITCH, PUSH; TYPE: standard, ACTION: NORMAL OPEN, HEAD STYLE: standard; FFT: ILLUMINATED; P/N: 35005543, OEM: MASCHINENFABRIK MOLLERS GMBH
174	855735	EA	MOTOR, GEARED	MOTOR, GEARED	MOTOR, GEARED; POWER RATING 1.10 KW, ELECTRICAL RATING 230/400 V, OUTPUT SPEED 1400/106 RPM, GEARBOX TYPE HELICAL, FFT: FOR ROLLER CONVEYOR, OEM: MASCHINENFABRIK BEUMER GMBH & CO KG OEM Part No: 36691, Mfr: SEW-EURODRIVE Mfr Part No: R37 D79054/BMG/H, MANDRG: 7390 Rev: 0 Item: 6, Equip/Tag Model No: 607-0011 Mfr: MASCHINENFABRIK BEUMER GMBH & CO KG, Equip/Tag Serial No: TP. 400 - 530 / 2400 - 2530 Mfr: MASCHINENFABRIK BEUMER GMBH & CO KG
175	1039903	KIT	KIT, ACTUATOR REPAIR	KIT, ACTUATOR REPAIR	KIT, ACTUATOR REPAIR; APPLICATION: HYDRAULIC DAMPER-VA WITH PNEUMATIC CYLINDER; FFT: KIT CONSISTS OF: 1) ITEM 9- SPLT RING; 2) ITEM 10- THREADED RING; 3) ITEM 11-O-RING; 4) ITEM 12- PISTON SEALING; 5) ITEM13- PISTON ROD SEALING; 6) ITEM 14- SCRAPER RING; 7) ITEM 16-O-RING; 8) ITEM 17- BUSH; 9) ITEM 18- SECURING RING; 10) ITEM 19-O-RING; 11) ITEM 24-PNEUMATIC-PISTON SEALING; 12) ITEM 25- PISTON ROD SEALING; 13) ITEM 26-O-RING; MODEL: BUW-510/1-E, MNFR: FRIEDRICH KROMBACH GMBH & CO.; DRAWINGS: BUW-OBM2-A.159240E - POS: 9, 10, 11, 12, 13, 1; TEST CERTIFICATE COMMENTS: MITC
176	814898	EA	CYLINDER, ACTUATING, LINEAR	CYLINDER, ACTUATING, LINEAR	CYLINDER, ACTUATING LINEAR: TYPE PNEUMATIC, Mfr: MASCHINENFABRIK MOLLERS GMBH Mfr Part No: 108092, MANDRG: DPL-1786021-4A Rev: 0 Item: 19.1, Tag/Equip No: 4-Z-3108-H, Equip/Tag Model No: DPL-1786021-4A, Equip/Tag Serial No: 18100
177	1638021	EA	DRIVE	DRIVE	DRIVE; POWER SUPPLY: 460 V 60 HZ, TYPE: PUT OUT, ENCLOSURE RATING: EXPLOSION PROOF, APPLICATION: MULTI TURN ACTUATOR; FFT: OUTPUT DRIVE COMPLETE A16.2-F16 WITH STEM NUT-BRONZE-LN-UN; A- UNBORGED; P/N: ARTICLE NO.: 2022.000 - Z000.367, POS NO.: 514.0 + 575.1, MNFR: AUMA RIESTER GMBH & CO KG, MODEL: ACTUATOR MODEL: SAEX 16.2 - F1.6, FOR TAG/EQUIP NO: 53-MV-4200/4250, COM NO.: 13330972, AUMA RIESTER GMBH & CO KG
178	471465	EA	GAUGE, VACUUM	GAUGE, VACUUM	GAUGE, VACUUM: RANGE 0-1 BAR, FFT: NO. 73350502000; EQPT: JW-0182; FOR FFS MACHINE; COMM. NO: 15.690, Mfr: MOELLER MASCHINEN Mfr Part No: 05 303 039
179	425576	ST	CYLINDER, ACTUATING, LINEAR	CYLINDER, ACTUATING, LINEAR	CYLINDER, ACTUATING, LINEAR; TYPE: DOUBLE ACTING PNEUMATIC, BORE: 80 MM, STROKE: 60 MM, RATING: 10 BAR; FFT: FOR PACKING UNIT W&H GERMANY; P/N: 35006122, MNFR: W&H GMBH, P/N: 35021952, MNFR: W&H GMBH, P/N: 45363.19.0060, MNFR: HERION USA INC, REFERENCE: OLD W 84 P/N: 028019
180	918114	EA	CABLE	CABLE	CABLE: TYPE MEASURING, FFT: FOR BOTTOM SEAM; APPLICATION: BAGGING MACHINE (WEIGHT: 25KG), Mfr: BEUMER MASCHINENFABRIK GMBH Mfr Part No: 7E060129
181	838156	EA	SWITCH, PROXIMITY	SWITCH, PROXIMITY	SWITCH, PROXIMITY; TYPE: INDUCTIVE SLOT SENSOR, SENSING RANGE: 0-15 MM, CONTACT RATING: 10-30VDC 200MA, SIZE: WD 48 X LG 30 X HT 60 MM, CLASSIFICATION: IP67, ACTION: PNP, CONNECTION: (3) WIRE CABLE; P/N: 35021150, MNFR: WINDMOLLER & HOLSCHER KG, REFERENCE: S115-K30-APX6, MNFR: TURCK INC

182	1553725	EA	MOTOR, BRAKE	MOTOR, BRAKE: POWER RATING 0.55 KW, ELECTRICAL RATING 460V 1.53A 60HZ 3PH 0.72PF, SPEED 1660/261 RPM, FRAME DT80K4, STANDARD IEC-34, FFT: TYPE: HELICAL WORM GEARED; P.O.NO: N8-M3-PO-90-2201SP, Suppl: MASCHINENFABRIK MOLLERS GMBH Suppl P/N: UNKNOWN, DRAWING: DPZ-060202-4F Rev: 0 Item: 1.1. Reference No: NM9064
183	850628	ST	BREAKER, CIRCUIT	BREAKER, CIRCUIT: TYPE MOTOR OVERLOAD PROTECTION, FFT: FOR FFS BAGGING MACHINE, OEM: WINDMOLLER & HOLSCHER KG OEM Part No: 04214322, Suppl: WINDMOLLER & HOLSCHER KG Suppl P/N: 04214322, MANDRG: B05 L00 Q00 E01 Rev: 0 Item: 1
184	234954	EA	CORD, ELECTRICAL	CORD, ELECTRICAL: TYPE SEAM CABLE BOTTOM, TERMINATIONS RINGS LUGS, FFT: FOR 660-ME-390-392-440-442 DIAMANT BAGGING MACHINE, PP II PLANT, Mfr: UNKNOWN Mfr Part No: 7E060124, Suppl: GOLDEN WING SUPPLY P/N: UNKNOWN, SABDRG: 7331.27.1750 Rev: 0 Item: 001, Reference No: AS4262861
185	1194312	ST	MOTOR, BRAKE	MOTOR, BRAKE: ELECTRICAL RATING 60 HZ, SPEED 1660/261 RPM, FFT: BEVEL GEAR BRAKE MOTOR FOR LINE J.L, M.COMM. NO.: 18100, HTS-CODE: 850151002, AS PER ATTACHMENT, OEM: MOELLER GMBH OEM PART NO: 21709552, MNFR DRG DPZ-0602032-4A Rev: 0 Item: 0.001
186	1208729	EA	MOTOR, BRAKE	MOTOR, BRAKE: POWER RATING: 1.1 KW, SPEED: 1455 RPM, ELECTRICAL RATING: 266 / 460 V; FFT: CURRENT : 3.85/2.20 A; 50 HZ; P/N: 21645237 (OLD); OEM: MASCHINENFABRIK MOLLERS GMBH, P/N: SPO05262 (NEW), OEM: MASCHINENFABRIK MOLLERS GMBH; DRAWING: DPL-1010622-4A, POS: 1.1
187	1656980	EA	CHAIN, POWER TRANSMISSION	CHAIN, POWER TRANSMISSION; STYLE: SIMPLE; PITCH: 3/4 IN; TYPE: ROLLER; MATERIAL: CARBON STEEL; LENGTH: 6534 MM; WIDTH: 16.5 MM; APPLICATION: STRETCH HOOD LIFTING FRAME; FFT: USE FOR STRETCH HOOD OF LINE#R, D; P/N: 21100494, MNFR: WINDMOLLER & HOLSCHER KG, SERIAL: COM.18.820; DRAWING: 5701450722-4A; REV. NA; POS: 100
188	523419	ST	CYLINDER, ACTUATING, LINEAR	CYLINDER, ACTUATING LINEAR: TYPE PNEUMATIC, BORE 80 MM, STROKE 60 MM, FFT: FOR NEW BAGGING MACHINE-C, MODEL: DIAMANT 1800-7331, LLDPE PHASE VII SPARE ITEMS, Mfr: WINDMOLLER & HOLSCHER KG Mfr Part No: 35006122, Suppl: NORGREEN LTD Suppl P/N: 35006122, DRAWING: 7331090000 Rev: 0, Serial No: 50154, Tag/Equip No: X-7101C
189	215336	ST	CYLINDER, ACTUATING, LINEAR	CYLINDER, ACTUATING, LINEAR: TYPE: DOUBLE ACTING-PNEUMATIC, BORE: 63 MM, STROKE: 100 MM, RATING: 16 BAR; FFT: MTL: DIE CASTING AND STEEL; FFS MACHINE; MODEL: 1166.000.001 #34710; BAGGING MACHINE BAG PRESSURE ROLLER (LY306) AND WELDING TONGS SWING ON (ZY0815ER-15690; (OLD P/N: 44630040100); W & H OLD# 02801382; P/N: 35006129, MNFR: W&H GMBH, REFERENCE: 44630040100, MNFR: LEIBFRIED; DRAWING: 7330.08.0100; POS: 67; DRAWING: 7334.29.010-1; POS: 0280-1382, 251-E/553/R; POS: 382
190	1250427	EA	MOTOR, ELECTRIC	MOTOR, ELECTRIC: POWER RATING 3-3.6 KW, ELECTRICAL RATING 400-460 VAC, TYPE VACUUM PRODUCER, SPEED 2880-3480 RPM, MOUNT FOOT, ENCLOSURE IP55, CONNECTION LOCATION TOP, INSULATION CLASS F, PHASE 3, STANDARD CE, DIN EN ISO 14001-2005, ISO 9001, FFT: FOR BAGGING MACHINES LINE A & D; POWER RATING: 4.02-4.83 HP; OEM: BECKER OEM PART NO: B05 D00 M00
191	951417	EA	UNIT	PIECE: TYPE CLAMPING, MATERIAL METAL, STANDARD DIN/ISO, Mfr: WINDMOLLER & HOLSCHER KG Mfr Part No: 04204968, DRAWING: 7335030503, 7335041200 Rev: 0 Item: 040, 003, Model/Machine No: 53.693
192	1553821	EA	MOTOR, BRAKE	MOTOR, BRAKE: POWER RATING 0.55 KW, ELECTRICAL RATING 460V 1.53A 60HZ 3PH 0.72PF, SPEED 1660/261 RPM, FRAME DT80K4, STANDARD IEC-34, FFT: TYPE:GEAR; P.O.NO: N8-M3-PO-90-2201SP, Suppl: MASCHINENFABRIK MOLLERS GMBH Suppl P/N: UNKNOWN, DRAWING: DPZ-6006002-4D Rev: 0 Item: 1.1. Reference No: NM9064
193	1624062	EA	CYLINDER, ACTUATING, LINEAR	CYLINDER, ACTUATING, LINEAR; TYPE: DOUBLE ACTING, BORE: 40 MM, STROKE: 5 MM, RATING: 10 BAR; P/N: 35021937, MNFR: WINDMOLLER & HOLSCHER KG
194	797977	EA	DISC, BRAKE	DISC, BRAKE: TYPE CONVEYOR, FFT: APPLICATION POSITIONING PALLET ROLLER CONVEYOR, FOR STRETCH HOOD, OEM: BEUMER MASCHINENFABRIK GMBH OEM Part No: 10003, Mfr: SEW-EURODRIVE Mfr Part No: BMG605
195	520579	ST	TRANSDUCER	TRANSDUCER: TYPE PRESSURE, INPUT 4-20 MA, OUTPUT 0-500 PSIG, FFT: FBC TYPE; FOR FBC PLANT, Mfr: FSI INTERNATIONAL LTD Mfr Part No: 745-001440-000, DRAWING: 012330402-63D Rev: 0
196	281145	EA	SWITCH, PUSH	SWITCH, PUSH; TYPE: PUSH-PULL, CONTACT RATING: 500 V, SIZE: WD 85 X LG 85 X THK 77.5 MM, COLOR: RED, MOUNT: SURFACE, HEAD STYLE: MUSHROOM, CLASSIFICATION: EX ED IIC TE, HOUSING: CLOSED, FFT: EMERGENCY STOP; EXPLOSION PROOF; ENCLOSURE: POLYIMIDE PLASTIC C*11 SEP 94; P/N: GHG 411 8101 R0855, MNFR: EATON, REFERENCE: GHG41181981008, MNFR: CEAG, REFERENCE: GHG4131, MNFR: ABB CEAG
197	1604250	EA	DIODE	DIODE: TYPE SEMI CONDUCTOR, WATTAGE 8889 KW, VOLTAGE 6500 V, AMPERAGE 790 A, TOLERANCE 5%, CONNECTION PRESS PACK, BODY STYLE P-N, FFT: FOR VARIABLE SPEED DRIVE; MNFR: WEG S.A. Mfr Part No: 1296551
198	915137	ST	MOTOR, GEARED	MOTOR, GEARED: POWER RATING: 0.55 KW, ELECTRICAL RATING: 230/460VAC 60HZ, PHASE: 3, OUTPUT SPEED: 1660 RPM, GEARBOX TYPE: HELICAL, CLASSIFICATION: F, MOUNT: FOOT, ENCLOSURE: TEFC; P/N: R47 D168 DRN80M4/02H, MNFR: SEW EURODRIVE, TEST CERTIFICATE COMMENTS: ROUTINE MOTOR TEST CERTIFICATE
199	566799	ST	RELAY, PNEUMATIC	RELAY, PNEUMATIC; TYPE: AIR LOCK/INPUT / OUTPUT CONNECTION: 1/2 IN/INPUT RANGE: 3-15 PSI/SUPPLY PRESSURE: 3-15 PSI/SUPPLY CONNECTION: 1/2 IN/CONTACT RATING: 250 V; P/N 30341, MNFR BTG SPECIALTY VALVES (CCI VALVE), P/N AL/CA-2-3, MNFR BTG SPECIALTY VALVES (CCI VALVE), P/N 85116440, OEM BTG SPECIALTY VALVES (CCI VALVE), SERIAL 282573-3, MNFR UNK
200	852478	EA	MOTOR, GEARED	MOTOR, GEARED: POWER RATING 0.37 KW, ELECTRICAL RATING 220/380 V, OUTPUT SPEED 1680/87 RPM, GEARBOX TYPE HELICAL, ENCLOSURE IP55, FFT-FOR LAYER PUSHING; AS PER DIN STANDARD, OEM: MASCHINENFABRIK BEUMER GMBH & CO KG OEM PART NO: 27637, MNFR: SEW-EURODRIVE MNFR PART NO: R37-DT1D4/BMG/TF, MNFR DRG 6581 Rev: 0 Item No: 18, TAG/EQUIP NO: 360-ME-405 / 455 MNFR: MASCHINENFABRIK BEUMER GMBH & CO KG, EQUIP MODEL NO: 607-0011 MNFR: MASCHINENFABRIK BEUMER GMBH & CO KG, EQUIP SERIAL NO: TP 400 - 530 / 2400 - 2530 MNFR: MASCHINENFABRIK BEUMER GMBH & CO KG, TEST CERTIFICATE COMMENTS: ROUTINE MOTOR TEST CERTIFICATE
201	923357	EA	MOTOR, GEARED	MOTOR, GEARED: POWER RATING: 2.2 KW, PHASE: 3, RATIO: 3.98-197.37, GEARBOX TYPE: HELICAL BEVEL, SHAFT: HOLLOW, MOUNT: FOOT; P/N: KA67 DRN100L4/BE2/V (NEW), MNFR: SEW-EURODRIVE GMBH & CO. KG, P/N: KA67 DV100M4 / BMG, MNFR: SEW EURODRIVE, P/N: 38036, SUPPL: BEUMER MASCHINENFABRIK GMBH; TEST CERTIFICATE COMMENTS: ROUTINE MOTOR TEST CERTIFICATE
202	1543213	EA	FAN	FAN: TYPE MOTOR COOLING, ELECTRICAL RATING 1.5 KW, MOUNT MOTOR SHAFT, MATERIAL AL, NUMBER OF BLADES 12, FFT: TO BE SUPPLIED WITH KEY WITH P/N: 00100137, MNFR: SEW EURODRIVE MNFR PART NO: 05929288, MNFR DRG PARTS LIST REV: 0 ITEM NO: 36
203	191181	KIT	KIT, ACTUATOR REPAIR	KIT, ACTUATOR REPAIR: TYPE O-RING, APPLICATION TEMPERATURE CONTROLLER, FFT: FOR TEMPERATURE CONTROLLER; FOR MODEL NO: DAB-D 4X2, DESUPERHEATER S/N: PM2788, Mfr: BTG SPECIALTY VALVES (CCI VALVE) Mfr Part No: 037858 999 000 VALVE 23
204	1198167	EA	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC: TYPE BOOSTER, INLET PRESSURE 14-140 PSI, OUTLET PRESSURE 280 PSI, CONNECTION NPT, BODY SIZE 1/4 IN, FFT: AS PER ATTACHMENT, MNFR: SMC CORP. MNFR PART NO: VBA1110-02GN
205	1606452	EA	FAN	FAN: TYPE COOLING, SIZE DIA 60 MM, ELECTRICAL RATING 24 V DC, MOUNT INTERNAL, MATERIAL PLASTIC, MNFR: SEW-EUR MNFR PART NO: 0816083X
206	719248	EA	DIAPHRAGM, ACTUATOR	DIAPHRAGM, ACTUATOR: ACTUATOR SIZE: 1 IN, RATING: ANSI 600 LM, SIZE: 3400IA, MATERIAL: RUBBER; FFT: FOR CONTROL VALVENOTE: SHELF LIFE IS REQUIRED AND MSDS (MATERIAL SAFETY DATA SHEET) REQUIRED, IF APPLICABLE; P/N: 1C0013152(NEW), MNFR: CCI, FOR TAG/EQUIP NO: 23-PV413A; DRAWING: 707211-17, POS: POS 15
207	158140	KIT	KIT, ACTUATOR REPAIR	KIT, ACTUATOR REPAIR: TYPE SOFT GOODS, APPLICATION SERVICE CONTROL VALVE, FFT: FOR SEVERE SERVICE CONTROL VALVES; MATERIAL: BUNA-NITON, Mfr: CONTROL COMPONENTS INC. Mfr Part No: 73516004, DRAWING: 701221-1 TO 701221-24 Rev: 0
208	1604078	EA	MOTOR, ELECTRIC	MOTOR, ELECTRIC: POWER RATING: 2.2 KW, ELECTRICAL RATING: 380 V; 4.85 A, SPEED: 1735 RPM, FRAME: 100L4, MOUNT: IMMA5, ENCLOSURE: IP55, INSULATION CLASS: F, PHASE: 3 PH; P/N: DRN 100L4M (NEW), MNFR: SEW EURODRIVE, SERIAL: 01.777628702.0001.12; TEST CERTIFICATE COMMENTS: MITC/TEST CERTIFICATES
209	821926	EA	MOTOR, GEARED	MOTOR, GEARED: POWER RATING 0.55 KW, OUTPUT SPEED 156 RPM, MOUNT FOOT, TYPE BRAKE, FFT: AMP 2.65/1.53; NM 31, FOR START STOP CONVEYOR, MNFR: SEW-EURODRIVE Mfr Part No: SA47/DRS71M4BE1, Serial No: 305127431.0002X98, For Tag/Equip No: 2V-3X32-ZV1A, Reference No: P-24-M1
210	874689	EA	COLUMN, ANALYSIS	COLUMN, ANALYSIS: MATERIAL SS 316, FFT: GAS CHROMATOGRAPH COLUMN HAYSEP N; LENGTH: 0.50 M; SIZE 100/120, TUBING SIZE 1/16 IN; Model# MAXUM-II, S/N: 5088990020, Equip# 81AT-6145, Mfr: SIEMAG (SMS) AG, Mfr Part No: COL1483
211	851799	EA	PROGRAMMABLE LOGIC CONTROL	PROGRAMMABLE LOGIC CONTROL: POWER SUPPLY: 100-240 V AC, APPLICATION: PIPELINE DELUMPER 24 IN; FFT: NUMBER OF DIGITAL INPUT: 12; NUMBER OF DIGITAL OUTPUT: 6; DISPLAY: LED; MNFR: FRANKLIN MILLER, P/N: EASY719-AC-RC, MNFR: MOELLER GMBH; ; TEST CERTIFICATE COMMENTS: MATERIAL TEST CERTIFICATE (MTC)
212	1248610	KIT	KIT, ACTUATOR REPAIR	KIT, ACTUATOR REPAIR: TYPE REPLACEMENT, COMPRISING SET OF GASKETS, APPLICATION ON OFF VALVE, FFT: FOR VALVE SIZE: 1/2 IN, RATING: CL 150; FOR HP UTILITY BOILER, MNFR: KPC CORPORATION MNFR PART NO: UNK, OEM: MACCHI S.P.A OEM PART NO: M110121002, MNFR DRG MAC-13100025-A101A Rev: 0 Item No: UNK
213	949751	EA	ACTUATOR, PNEUMATIC	ACTUATOR, PNEUMATIC; TYPE: MODULAR, TRAVEL: QUARTER TURN 90 DEG, PRESSURE RATING: 40-120 PSI G, OPERATED: FAIL TO CLOSE, BENCH RANGE: 3-15 PSI G, APPLICATION: SAUNDERS DIAPHRAGM VALVE(SIZE 40 MM); FFT: STANDARD: DIN 3337; MNFR: SAUNDERS VALVE CO LTD
214	504225	EA	FLASHLIGHT	FLASHLIGHT: TYPE XENON BEACON, POWER RATING 12/24 VDC, FFT: MODEL NO.: XENOFASH 21FE; USED AT INITIATOR STORAGE CELL DOOR; FOR LDPE, Mfr: AL-BILAD FIRE FIGHTING SYSTEMS Mfr Part No: 63818, Mfr: SIRENA Mfr Part No: XF211FE, Mfr: SIRENA S.P.A./MINICELERE Mfr Part No: XF211FE12240A3
215	671173	EA	ACTUATOR, HYDRAULIC	ACTUATOR, HYDRAULIC; TYPE: GOVERNOR, OPERATED: OIL PRESSURE, RATING: 7.6 L/MIN; FFT: HYDRAULIC; FOR ELECTRONIC GOVERNOR K-1301 & K-1601; EXTRACTION WOODWARD PART NO: A9904-041; P/N: EG-10P, MNFR: WOODWARD GOVERNOR CO.; DRAWING: 8924506, 9930748 & 9988266
216	197298	ST1	FLASHER	FLASHER, ELECTRICAL RATING: 200 A 2500 W 60 HZ, CONNECTION: (3) BLADE TERMINAL, POWER SUPPLY: 120 V AC, OPERATION: AUXILIARY MODULES , TYPE: BEACON; FFT: SOLID STATE FLASHER AND CONTROL; 1 SET=2 PCS; FLASH RATE 90PPM STANDARD : CSA; P/N: FS 155-30T & FS 155-30RF, MNFR: ABB SSCAC, 024/856, POS: 017
217	1647645	EA	RELAY	RELAY; COIL VOLTAGE: 24 V AC, ACTION: 4 PDT, CONTACT RATING: 7A/6A, 230VAC/250VAC, TYPE: MINIATURE INDUSTRIAL, CONTACT ARRANGEMENT: 4 CO, MOUNT: RAIL MOUNTED, ENCLOSURE: IP40, TERMINAL: (14) BLADE, CONTACT MATERIAL: AG Ni; P/N: R4N-2014-23-5024-WTL, MNFR: RELIUM S.A., TEST CERTIFICATE COMMENTS: REQUIRED
218	717641	EA	CAPACITOR	CAPACITOR: TYPE: FIXED, VOLTAGE: 370 V AC; P/N: 610-803-34(OLD), MNFR: MARC-CLIMATIC CONTROLS INC.; P/N: 610-805-34, MNFR: MARC-CLIMATIC CONTROLS INC
219	960077	EA	BATTERY, PACK	BATTERY, PACK: TYPE NICA D, VOLTAGE 7.5 V DC, AMP HOURS 1600 MAH, FFT: HIGH CAPACITY; FM/CSA: INTRINSICALLY SAFE; FOR P7100, STANDARD: FM, CSA, MNFR: HARRIS MNFR PART NO: HTPA7Y
220	1604084	EA	SWITCH, NETWORK	SWITCH, NETWORK: TYPE MANAGED ETHERNET, PORT/QUANTITY 10/100 BASE TX, CABLE TYPE RJ45, ELECTRICAL RATING 12-48 V DC, CURRENT/INPUT 0.41 A, FREQUENCY/INPUT 800 MEG HZ, VOLTAGE/INPUT 24 V DC, STANDARD CE 508, EN 61000-4-2, MNFR: MOXA INC MNFR PART NO: IMC-21-SC
221	418390	EA	COOLER	COOLER: TYPE THERMOSTATIC, RATING 150 PSI G, FFT: VORTEX COOLER SYSTEM, RANGE: 1 1/4 X 6 1/2 X 5 IN, SERIAL NUMBER: 7440
222	857846	EA	FUSE	FUSE: TYPE CONTROL, AMPERAGE 5 A, VOLTAGE 600 V, CARTRIDGE FIBER GLASS, CONNECTION FERRULE, SIZE DIA 13/16 X LG 2-1/4 IN, CLASSIFICATION J, STANDARD CSA; UL, FFT: TIME DELAY, OEM: U.S. FILTER OEM Part No: 11290715, MANDRG: 16212151 Rev: 0 Item: 9, Model/Machine No: LPI SERIES Mfr: BUSSMANN, Equip/Tag Model No: GRAB STYLE RAKE Mfr: UNKNOWN, Equip/Tag Serial No: CH11002 Mfr: UNKNOWN
223	959974	EA	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC: TYPE SELF-ACTING PRESSURE, INLET PRESSURE 1 MPA, OUTLET PRESSURE 0.05-0.85 MPA, CONNECTION RCTD, BODY SIZE 3/8 IN, BODY MATERIAL POLYCARBONATE, MNFR: SMC CORP. MNFR PART NO: AW30-03BG1-B
224	270963	EA	ELECTRODE	ELECTRODE; TYPE: IGNITOR TIP, APPLICATION: FOR ZURN INDUSTRIES BOILERS, SIZE: LG 34 IN, CONNECTION: MPT 1/2 IN; P/N: 33020-1005, MNFR: ZURN INDUSTRIES INC., P/N: CFM200.14, MNFR: DAYTON, MODEL: 6B7Y4, SERIAL: 3635/6; 125, AOE-753, POS: 12+4
225	566798	ST	RELAY, PNEUMATIC	RELAY, PNEUMATIC; TYPE: AIR LOCK/INPUT / OUTPUT CONNECTION: 1/4 IN/INPUT RANGE: 3-15 PSI/SUPPLY PRESSURE: 3-15 PSI/SUPPLY CONNECTION: 1/4 IN/CONTACT RATING: 250 V; P/N 85101913 (NEW), MNFR BTG SPECIALTY VALVES (CCI VALVE), P/N AL/CA-2-3, MNFR BTG SPECIALTY VALVES (CCI VALVE), P/N 85116440, OEM BTG SPECIALTY VALVES (CCI VALVE)
226	1077192	EA	ASSEMBLY	ASSEMBLY: TYPE PILOT, APPLICATION FLARE, Mfr: ZECO INC Mfr Part No: H5LF-2-HEI-27/C, Mfr Drg VD-SST-6001-0003 (CS-8690) Rev: UNK Item No: A001, Reference No: TYPE H5LF-2-HEI-27/C Mfr: UNKNOWN, Equip Model No: WC_5178_54 / MB_2230 / WC_5178_54 / WC_5178_54 / NA_1555
227	852816	EA	FUSE	FUSE: TYPE BLOWN FUSE-INDICATOR, AMPERAGE 2 A, VOLTAGE 500 V, CARTRIDGE CERAMIC, CONNECTION FERRULE, SIZE DIA 10.3 X LG 38 MM, CLASSIFICATION AM, STANDARD IEC, FFT: FOR UPS, OEM: FERRAZ SHAWMUT OEM Part No: AM 10 X 38 2A, Mfr: CHLORIDE FRANCE SA Mfr Part No: 0108050015
228	1225017	EA	BLOWER	BLOWER: CAPACITY 1,500 NM3/HR, FFT, MNFR: DONGYANG MNFR PART NO: EA2 150, MNFR DRG VD-SW-3003-0258 Rev: N/A ITEM NO: D11338
229	693795	EA	CIRCUIT	CIRCUIT: TYPE DUAL ION ZONE, APPLICATION FIRE ALARM SYSTEM, Mfr: PYROTRONICS Mfr Part No: ZU1-35
230	279670	EA	MOTOR, GEARED	MOTOR, GEARED: POWER RATING: 0.75 KW, ELECTRICAL RATING: 266/460VAC 3.15/1.83A 60HZ, PHASE: THREE, OUTPUT SPEED: 1680/75 RPM, RATIO: 22.7:1, GEARBOX TYPE: HELICAL GEAR MOTOR, CLASSIFICATION: IP55, MOUNT: M1 (B3), ENCLOSURE: IE3, TYPE: BRAKE; FFT: VB-266V; NM-5 RECTIFIER - BGE 1.5; USED FOR FOIL M/C LIFTING FRAME; A - 08 Dec 99; (OLD P/N: R43D780N4BMG) STANDARD : CE; IEC 34; P/N: R37 DRN80M4/BE1Z, MNFR: SEW EURODRIVE, P/N: R37 DRS8054BE1Z, MNFR: SEW EURODRIVE, SERIAL: 30617450010007999
231	437047	EA	ACTUATOR, PNEUMATIC	ACTUATOR, PNEUMATIC; MATERIAL: CS; FFT: ACTUATOR MDL: AW205; ON-OFF CONTROL BALL VALVES SIZE: 8 IN; VALVE MDL: AW205-E0108-62; VALVE SERIAL NO: A-709839; FOR VALVE TAG NO: 91-HV-5371; P/N: 17899, MNFR: KITAMURA VALVE MFG CO. LTD, MODEL: AW205-E0108-62; DRAWING: CA-26K

232	401046	ST	MODULE	MODULE, TYPE: OPTO-COUPLER, INPUT: 10-53 V DC, OUTPUT: 24-253VAC 4A, APPLICATION: TYING MACHINE, FFT: TYPE AMMS FOR SECTION & BAR MILL TYING MACHINES; P/N: 50034, MfNR: MURRELEKTRONIK GMBH
233	491172	EA	DETECTOR, RESISTANCE TEMPERATURE	RTD: TYPE DOUBLE, RESISTANCE 100 OHM, WIRE 3, STEM SIZE OD 6 X LG 892 MM, FFT: FOR REACTOR; SPRING LOADED MOUNTINGS; TERMINALS (2-WHITE 4-YELLOW); PROD NO: 22606-892, MfNR: THERMO ELECTRA, NETHERLANDS MfNR Part No: P4796002001
234	707442	ST1	FUSE	FUSE: TYPE FAST ACTING, AMPERAGE 0.25 A, VOLTAGE 250 V, CARTRIDGE GLASS, CONNECTION FERRULE, SIZE DIA 6.3 X LG 32 MM, STANDARD CSA; UL, FFT: 5 PCS/BOX, MfNR: DONALDSON MfNR Part No: P13-5712, MfNR: WAUKESHA-PEARCE INDUSTRIES, INC. MfNR Part No: P13-5712, Drawing 3EA-42024-00 Rev: 0 Item No: 73, Reference No: 0312.250VXP MfNR: LITTELFUSE, Reference No: 312 1/4A 250V MfNR: LITTELFUSE, Reference No: AGC 0.25 MfNR: BUSSMANN
235	1545727	EA	PRINTHEAD	PRINTHEAD, TYPE: INTELLISEAG, APPLICATION: LABEL PRINTING, FFT: STANDARD - POWER SUPPLY AUTO RANGING SWITCHING TYPE; P/N: KIT-217-12TAF8-DMX, MfNR: DATAMAX-O'NEIL, REFERENCE: 1127 0
236	964798	ST	FIXTURE, FLUORESCENT LIGHTING	FIXTURE, FLUORESCENT LIGHTING; VOLTAGE: 110-250 V AC, WATTAGE: 26 W, LENGTH: 95 MM, LAMP: 1, MOUNT: PANEL, SIZE: WD 345 X HT 55 MM, STANDARD: CE; VDE; FFT: USED AT CMC-CGL WELDER CONTROL PANEL; UNIVERSAL LIGHT UNIT; P/N: P5155.100(OBSOLETE), MfNR: RITTAL GMBH & CO KG, P/N: S24155.010, MfNR: RITTAL GMBH & CO KG
237	1049772	EA	CAPACITOR	CAPACITOR: CAPACITANCE 25/7.5 MICRO F, VOLTAGE 440 V, FFT: FOR AIR CONDITIONER, OEM: FRIEDRICH AIR CONDITIONING CO OEM Part No: 61080547, Equip Model No: 5H2030-B
238	1037848	EA	ASSEMBLY	ASSEMBLY: TYPE PRESSOSTATIC HEAD, APPLICATION 3 WAY VALVE, FFT: FOR SF6 AMMONIA CONTROL VALVES EHSS ENTITIES, MfNR: CCI CONTROL COMPONENTS INC. MfNR Part No: 61702, MfNR: STI MfNR Part No: UNK, Drawing 201201-10CH Rev: 0 Item No: AL, Serial No: 201201-10CH, Model/Machine No: AL_102, TEST CERTIFICATE NEEDED
239	37617	EA	DIAPHRAGM, ACTUATOR	DIAPHRAGM, ACTUATOR SIZE: # 2A, SIZE: OD 12-1/4 IN, FFT: TYPE B; TOP 2 AC, WITH 12 BOLT HOLES, FOR WATER TREATER UNIT; P/N: 16-2A, MfNR: SAUNDERS VALVE CO LTD
240	681218	EA	INDICATOR	INDICATOR: TYPE WEIGHING, SIZE 3.09 X 5.75 X 10 IN, RANGE 4-20 MA, MOUNT PANEL, FFT: FOR WEIGHING INSTRUMENTS USED WITH LOAD CELL MODEL NO: USPL5-A; PART NO: S501-0044; 50001B CAPACITY; WEIGHT CONVERTER MODEL NUMBER: H12151/30WC-M1; OPTION: B1; DISPLAY: 6 DIGIT LCD; RESOLUTION: 1.985,000; OUTPUT: 4-20 MADC; POWER: 120 VAC; STANDARD FEATURES: GROSS OR NET MODES, MENU DRIVEN CALIBRATION, FRONT PANEL DIAGNOSTICS, POWERS UP TO 8, 350 OHM LOAD CELL, BI-DIRECTIONAL RS-232C PORT, NTEP CERTIFIED, AUTO ZERO TRACKING, MOTION DETECTION, WATERPROOF KEYBOARD, TWO RELAY CONTACTS; WEIGHT: 4.5 LBS, MfNR: HARDY INSTRUMENTS MfNR Part No: H12151/30WC-A1-B1-E3
241	88009	ST	DISTRIBUTOR	DISTRIBUTOR: TYPE BOTTOM ARM, FFT: MATERIAL: EBONITE; FOR ANION, MfNR: TERMOKIMIK CORPORATION MfNR Part No: UNKNOWN, DWG: 24902-D20-2-03 Rev: 0 Item: POS:3
242	979369	ST1	FAN	FAN: TYPE AXIAL FLOW, SIZE 8534 MM, ELECTRICAL RATING 92.7 KW, VOLUME RATING 374.9 M3/S, MATERIAL FRP, FFT: SPEED: 122.89RPM, NO OF BLADES: 8, MANUAL ADJUSTABLE PITCH; FOR COOLING TOWER; COFIMCO ORDER NO: 30943/000158 POSS., BLADE SIZE (LENGTH) 280 CM, FAN BASE DIAMETER 212 CM, MfNR: COFIMCO SPA, ITALY MfNR Part No: 300.01/01, Model/Machine No: 8534-08-33F/G20T MfNR: COFIMCO SPA, ITALY
243	1051951	EA	FAN	FAN: TYPE COOLING, FFT: FOR INDUCTION MOTOR, MfNR: HYUNDAI HEAVY INDUSTRIES MfNR Part No: 0A797-C06-002-CF, Equip Serial No: 0A797-C06-002, Equip Model No: PLS131SR208KYAN
244	1604485	EA	BOARD, PRINTED CIRCUIT	BOARD, PRINTED CIRCUIT: TYPE KFB-ENCFW09 MOUNTED, FUNCTION FEEDBACK BOARD, VOLTAGE 125 V DC, CURRENT 2 A, FFT: KIT COMMUNICATION BOARD, FOR VARIABLE-SPEED DRIVE, STANDARD: IEC, MfNR: WEG S.A. MfNR PART NO: 10933495, SUPPL: BUSINESS TRIBUNE CO LTD, SUPPL Part No: UNKNOWN, TAG/EQUIP NO: 84-SEE-074, 84-SEE-076, TAG/EQUIP NO: MVM01 C080 T 4160, MVM01 C120 T 4160
245	901844	EA	MODULE	MODULE: TYPE COMMUNICATION OPTION CARD, APPLICATION PALET/PAC/ FOLIO/PAC/ THERMOPAP, FFT: OPTION CARD; RS-485 + SBUS FOR CONTROL AND DIAGNOSTICS, OEM: MASCHINENFABRIK BEUMER GMBH & CO KG OEM Part No: 50481, MfNR: SEW-EURODRIVE MfNR Part No: F5C11B, MANDRG: 5828, 6479 Rev: 0
246	784036	EA	CONTACT	CONTACT: AMPERAGE 260 A, VOLTAGE 480 V, STANDARD CE-UL, FFT: FOR AUTOMATIC TRANSFER SWITCHES 7ACTBC3150NSC & 7ACTBC3260NSC AT UTILITIES/OFFSITE, MfNR: AUTOMATIC SWITCH COMPANY (ASCO) MfNR Part No: 715197-001
247	863357	EA	AMPLIFIER	AMPLIFIER: TYPE: ELECTROMETER, INPUT: 440V, POWER RATING: 100 A
248	727103	EA	SENSOR	SENSOR: TYPE METHANE/FLAMMABLE, RANGE 0-100 PCT LEL, FFT: 0 TO 100% LEL METHANE FLAMMABLE SENSOR FOR DETECTIVE PORTABLE DETECTOR, MfNR: CROWCON DETECTION INSTRUMENTS LTD MfNR Part No: 5011375, Model/Machine No: DETECTIVE
249	1627122	EA	AIR CONDITIONER	AIR CONDITIONER: TYPE: PANEL, CAPACITY: 3753 BTU/H, REFRIGERANT TYPE: R 134A, RATING: 2050 W, ELECTRICAL RATING: 460 V AT 60HZ; P/N: 13383636178, MfNR: PFANNENBERG INC., MODEL: DTS 3185, SERIAL: S13440828107, TEST CERTIFICATE COMMENTS: TEST CERTIFICATE NEEDED
250	270686	EA	MOTOR, GEARED	MOTOR, GEARED: POWER RATING: 0.55 KW, ELECTRICAL RATING: 266/460VAC 2.65/1.53A 60HZ, PHASE: THREE, OUTPUT SPEED: 82 RPM, RATIO: 1660:82, GEARBOX TYPE: WORM, MOUNT: H1A SHAFT, ENCLOSURE: IP55, TYPE: BRAKE, FFT: RECTIFIER TYPE: BGE 1.5, INSULATION CLASS: H; USE FOR REJECTION STATION CONVEYOR; KOM NO#17.215. USED TAG/CNVR:7107A/B/C/D/E/F-M1; BRAKE VOLTAGE = 266VAC GNM STANDARD : CE; IEC 34; P/N: SA47 TD180K4BMG, MfNR: SEW EURODRIVE, SERIAL: 01.3073193403.0001X02, DRAWING: DP2-070002-4E
251	1573364	EA	TRANSDUCER	TRANSDUCER: TYPE PRESSURE, INPUT 5 V DC, OUTPUT 0.5 - 4.5 V DC, SUPPLY 0-200 (SEALED GAUGE) PSI, APPLICATION HVAC CHILLED WATER, FFT: MICRO CONTROL SYSTEMS, MfNR: MCS MfNR PART NO: MCS-200C-20
252	854121	EA	REGULATOR	REGULATOR: TYPE: PRESSURE, RATING: 0.8-6 BAR, CONNECTION: FNPT 1/4 IN, FFT: FOR MAINTENANCE DEVICE; TYPE: COMPRESSED STANDARD : CE; P/N: B18-C2-FLOO (OLD), MfNR: WILKERSON CORPORATION, P/N: B18-C2-FLOOB (NEW), MfNR: WILKERSON CORPORATION, P/N: 15034049, OEM: WERNER & PFEIDERER, MfNR DRG: 50983-1041H80, POS: 1
253	1000566	EA	CONVERTER, FREQUENCY	CONVERTER, FREQUENCY: TYPE: MOVDRIVE, INPUT: 380-500VAC 14.4A 50/60HZ 3PH, OUTPUT: 7.5 KW, CONSTANT OUTPUT CURRENT: 16 A, KVA RATING: 11.2 KVA, SIZE: WD 105 X HT 335 X DP 294 MM, APPLICATION: VSD MOTOR, STANDARD: UL; FFT: POWER LOSS: 290W; NO. OF SLOTS: 3; SIZE: 25; WITH LINE FILTER; MfNR: COPERION WAESCHLE GMBH & CO KG, P/N: MDX61B0075-5A3-4-00 8279624, MfNR: SEW EURODRIVE
254	219654	ST	CONTROLLER, ELECTRONIC	CONTROLLER, ELECTRONIC: TYPE: TEMPERATURE, MOUNT: PANEL, ELECTRICAL RATING: 100-250VAC 6VA 50/60HZ, APPLICATION: H2 PURIFIER, FFT: INPUT = AC 120V/240V; SENSOR 1C; WITH SOLID STATE RELAY; FOR JOHNSON MATTHEY H2 PURIFIER MODEL: HP25 STANDARD : CE; UL; P/N: 14-003160-408, MfNR: ATHENA CONTROLS INC, P/N: 16ICSY10AC, MfNR: ATHENA CONTROLS INC, P/N: 8819, MfNR: FOXBORO CO. U.S.A., P/N: XT 16, MfNR: ATHENA CONTROLS INC; DRAWING: B1_252, POS: 358
255	946819	EA	REGULATOR	REGULATOR: TYPE AUTOMATIC INSERTION, RATING 300 LB, CONNECTION FLANGE RF, BODY SIZE 1-1/2 IN, FFT: SEAT: TEFLON; INSERTION: 42 IN; MAX WORK PRESSURE: 220 PSI; PROBE SIZE: 1-1/2 IN; MATERIAL: SS 316; PROBE RATING: 0-50 PSI, OEM: WELKER OEM PART NO: IRA4ST0XC42NGHD, MODEL/MACHINE NO: IRA-45SF, TEST CERTIFICATE COMMENTS: MATERIAL TEST CERTIFICATES TO BE PROVIDED
256	713066	EA	ASSEMBLY	ASSEMBLY: TYPE ROTOR, FFT: CONSIST OF: WHEEL ASSEMBLY AND SHAFT ASSEMBLY; FOR COPPUS TURBINE (2GT-1601), MfNR: COPPUS ENGINEERING CORPORATION, USA MfNR Part No: UNKNOWN, Model/Machine No: RLVA-20L MfNR: UNKNOWN, Serial No: 97T3502 MfNR: UNKNOWN
257	942878	ASV	ASSEMBLY	ASSEMBLY: TYPE POWER END, APPLICATION HP SCRUBBER PUMP, FFT: COMPLETE WITH CRANK MECHANISM, MfNR: PERONI POMPE SPA, ITALY MfNR Part No: UNK, MANDRG: 313H N2 000 N1 SF2 Rev: 0 Item: 1-54, Reference No: COD: 313H N2 SF2 000 MNV, Equip/Tag Model No: 3130N [5 70 X 95]
258	966857	EA	TERMINAL	TERMINAL: TYPE: FIXED, SIZE: 2.5 MM2, MATERIAL: PLASTIC, RATING: 400 V; FFT: FOR SQUIRREL CAGE INDUCTION MOTOR MODEL NUMBER: DT71-DV1325/TF STANDARD : CSA; P/N: 1823337, MfNR: SEW EURODRIVE
259	261369	EA	MODULE	MODULE: TYPE CONTROL ELECTRONIC, FFT: FOR CHILLER UNIT TYPE DTC COND- DTC-ELECTRONIC FOR CHILLER UNIT TAG # X-9101 TO 9108 FOR USE ON COMPRESSOR MODEL#K1000CS, MfNR: DORIN MfNR Part No: 2CE3010, Suppl: V-LINE EUROPE EXPORT MARKETING GMBH Suppl P/N: UNK, DRAWING: 89265 S/1-64 Rev: 0
260	788739	EA	MOTOR	MOTOR, RATING: 230/280 V AC, TYPE: FAN, SPEED: 1100 RPM, ROTATION DIRECTION: RIGHT, FFT: OLD P/N: 618-714-45; P/N: 618-714-66, MfNR: MARC CLIMATIC CONTROLS INC., FOR TAG/EQUIP NO: RCG36-21, RCG35-21, EQUIP SERIAL NUMBER: PRACCB812585401; PRACCB812585299; CATALOGUE: RCG35-21, POS: 01
261	693812	EA	DETECTOR, FIRE PROTECTION	DETECTOR, FIRE PROTECTION: TYPE IONIZATION SMOKE, FFT: FOR FIRE ALARM SYSTEM, MfNR: PYROTRONICS MfNR Part No: D1-4A
262	1671170	EA	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC: TYPE: PRESSURE REDUCER, INLET PRESSURE: 1240 PSI G, OUTLET PRESSURE: 75-190 PSI G, CONNECTION: 1 IN FNPT, BODY MATERIAL: SS, OPERATING TEMPERATURE: 200 °F, FFT: CV = 2.5, FOR IC4 TANK; P/N: 60HP10056/PT56W5A1S6M, MfNR: JORDAN VALVE
263	1527471	EA	LAMP	LAMP: TYPE LED, PILOT, WATTAGE 1.3 W, VOLTAGE 130 VDC, COLOR RED, STANDARD UL, FFT-FOR MV SWITCHGEAR, MfNR: LEDTRONICS MfNR PART NO: RPLB-0201-130V1402 5L, MfNR DRG 82517-1-D4 (33-E-4001) REV: 2 ITEM NO: 40, MfNR DRG 82517-2-D4 REV: 2 ITEM NO: 39
264	1040586	EA	DRIVER, SPEAKER	DRIVER, SPEAKER: TYPE: WEATHERPROOF RATING: 100 W; P/N TS100, MfNR FEDERAL SIGNAL CORP
265	1527473	EA	LAMP	LAMP: TYPE LED, PILOT, WATTAGE 1.3 W, VOLTAGE 130 VDC, COLOR WHITE, STANDARD UL, FFT-FOR MV SWITCHGEAR, MfNR: LEDTRONICS MfNR PART NO: RPLB-0209-130V1402 5L, MfNR DRG 82517-1-D4 (33-E-4001) REV: 2 ITEM NO: 42
266	1545167	EA	FAN	FAN: TYPE COOLING, SIZE WD 20 MM, SPEED 3550 RPM, ELECTRICAL RATING 380V, 60 HZ, MOUNT DN, CLASSIFICATION EX D IIB T4, ENCLOSURE RATING IP55, MATERIAL PLASTIC, APPLICATION MOTOR, STANDARD CE, FFT-MOTOR RATING: 7.5 KW; FRAME SIZE: 160M, MfNR: HYUNDAI HEAVY INDUSTRIES MfNR PART NO: 159C8730AA-1, DRAWING LV MOTOR REV: 0 ITEM NO: 1
267	435441	EA	BASE, RELAY	BASE, RELAY: TYPE (11) PIN TIMER, ELECTRICAL RATING 250VAC 10A, STANDARD CSA; UL, FFT: FOR H38A TIME DELAY RELAY ON AEL-0101 ELEVAOR; REF:CIW-87-0904, MfNR: NIPPON ELEVATOR MFG CO LTD MfNR Part No: P2CF-11, Reference No: P2CF-11 MfNR: OMRON CORPORATION, JAPAN
268	270798	EA	MOTOR, ELECTRIC	MOTOR, ELECTRIC, POWER RATING: 0.75 KW, ELECTRICAL RATING: 460VAC 60HZ, SPEED: 1730 / 60 RPM, MOUNT: M1A, INSULATION CLASS: H, PHASE: THREE, FFT: V8-266V NM-10 RECTIFIER TYPE BGE 1.5, USED FOR TRANSFER CONVEYOR, MOLLER, KOM NO#17.215; LDPE SPARE ITEMS; P/N: SA57/TDRN80MK4/BE, MfNR: SEW EURODRIVE; DRAWING: DTF0100092-4E
269	855186	EA	MOTOR, ELECTRIC	MOTOR, ELECTRIC, POWER RATING: 185 KW, ELECTRICAL RATING: 4000VAC WITH 3 CABLES; 60HZ, TYPE: SQUIRREL CAGE, SPEED: 1780 (RATED) RPM, FRAME: HGF 5009/10/11T, MOUNT: F-1, ENCLOSURE: IPW55, INSULATION CLASS: F, TEMPERATURE CLASS: CLASS B AT SERVICE FACTOR 1.00, PHASE: 3, DIRECTION: BOTH, STANDARD: NEMA; FFT: FOR FAN; OUT PUT: 250 HP (185KW); POLE: 4; RATED CURRENT: 32.9A; RATED TORQUE: 1000 NM; SERVICE FACTOR: 1.15; COUPLING: DIRECT; ENCLOSURE MATERIAL: CAST IRON; WITH STAINLESS STEEL EXTENDED GREASE NIPPLE (DE & NDE) & WITH STEEL EXTENDED GREASE OUTLET; MfNR: SPX CORP, P/N: HGF 5009, MfNR: WEG ELECTRIC MOTORS CORP., SUPPL: HANSEN TRANSMISSION, SERIAL: 914674024; MfNR DRG: 9303.2797
270	251770	EA	SWITCH, SELECTOR	SWITCH, SELECTOR: TYPE OFF-ON START, ACTION 3PST, CONTACT ARRANGEMENT 2NO-1NC, POSITION 3, FFT: INSTALLED IN PUSH BUTTON STATION, FOR 200-MP-13 A/B 760-MP-01 A/B, 1 POSITION SPRING RETURN, MfNR: UNKNOWN MfNR Part No: EFS3 310R 50.15.21.01, MfNR: COMELECTRIC MfNR Part No: UNKNOWN
271	706648	EA	ASSEMBLY	ASSEMBLY: TYPE TEMPERATURE CONTROLLER, FFT: RANGE: 60DEG C/140DEG F, MfNR: ANALYZER TECHNOLOGY INTERNATIONAL MfNR Part No: 3/8-TV/SC-1-140-5
272	676539	EA	RELAY, CONTROL	RELAY, CONTROL: TYPE: 27 D, UNDER VOLTAGE RELAY, APPLICATION: ELECTRIC POWER DISTRIBUTION SYSTEM, SUPPLY: 125 V D C, ELECTRICAL RATING: 48/125 VDC, 50/60 HZ, MOUNT: DRAW-OUT, PANEL, COIL VOLTAGE: 120 V; P/N: 411R4175-DP, MfNR: BROWN BOVERI COMPANY GERMANY
273	421047	ST	SWITCH, TEMPERATURE	SWITCH, TEMPERATURE; CONTACT RATING: 120 V AC, RANGE: 300VA, CAPILLARY LENGTH: 400 DEGREES, BULB SIZE: 215", TYPE: MOTOR PROTECTOR , CONTACT ARRANGEMENT: PROTECTOR, APPLICATION: MODULE FOR SEMI SEALED COMPRESSOR OR EQUIVALENT FOR SUBSTATION 09-1 OR A/C 1 & 2; FFT: EQPT. TAG# SUBSTATION 09-1 YORK A/C 1 & 2, FOR USE IN LDPE.; MODEL#: MP33-1010; SOLID STATE CUT-OUT 2200EFG, CUT-IN 190 DEG F, 300VA AT 120 VAC, AUTOMATIC RESET REPLACES MODEL# MP23-1043; P/N: MP33-1010 3433-043, MfNR: ROBERTSHAW
274	28618	ST	MOTOR, BRAKE	MOTOR, BRAKE; POWER RATING: 7.5 HP, SPEED: 1730 RPM, TORQUE: 55.3 LB FT, ELECTRICAL RATING: 230/460VAC 19.9/5A 60HZ, STANDARD: CE; CSA; FFT: ENCLOSURE: TFC/B; FLANGED MOUNTED; S/O 890121003.96.96.00; CONNECTION: STARSTAR/STAR; MfNR: SEW EURODRIVE, REFERENCE: DFV 132848M6 15 MR-KS(OLD), MfNR: SEW EURODRIVE, REFERENCE: DFV132548M68HR-KS(OLD), MfNR: SEW EURODRIVE, REFERENCE: DRN13254/BE11HR/FG (NEW)
275	1600312	EA	DETECTOR, RESISTANCE TEMPERATURE	DETECTOR, RESISTANCE TEMPERATURE: TYPE MINERAL INSULATED, RESISTANCE 100, TEMPERATURE RATING 0-600 °C, SHEATH MATERIAL SS 316, WIRE 3 DUPLEX, HEAD EXPLOSION PROOF GR IIA, IIB, STEM SIZE U LG 415 (350 MM) + 65 MM (THREAD) MM, PROCESS CONNECTION NIPPLE 1/2 IN NPT X 100 MM X SS 304 (SPRING LOADED), SHEATH DIAMETER 6.35 MM, MfNR: PROCEMI TEMPERATURE & ELECTROMECH. CO. W.L.L MfNR PART NO: UNKNOWN, SPECIFICATION SF20-341S-005 REV: 0 ITEM NO: 2-TEE15
276	26960	M	TRAY, CABLE	TRAY, CABLE: TYPE STRAIGHT, SIZE WD 300 X HT 100 X LG 6000 MM, FFT-WITH COVER, MfNR: ABRAHAIN COPEL LTD. MfNR PART NO: 1R100J4-300S1-3.00V
277	235628	EA	MOTOR, GEARED	MOTOR, GEARED: POWER RATING 1.5 KW, ELECTRICAL RATING 220/380VAC 6.5/3.75A 60HZ, OUTPUT SPEED 1710/1320 RPM, TYPE BRAKE, FFT: FOR PALLETIZING LINE, SLIDING PLATE FRAME WITH TOOTHED BELT, PP II PLANT STANDARD : IEC 34, OEM: MOELLER GMBH OEM PART NO: UNK, MfNR: SEW EURODRIVE MfNR PART NO: SA57 DRN90L4/BE2 (NEW), DRAWING DPL-104022-4B REV: 0 ITEM NO: 1.1, TAG/EQUIP NO: 660-ME-402/452

278	567287	EA	SWITCH, SAFETY	SWITCH, SAFETY: ACTION DPDT, TYPE MANUAL, CLASSIFICATION CL1 GR BCD; CL2 GR EFG, CONTACT RATING 125/250VAC 10A, STANDARD UL, FFT:EXP/WP MANUAL FIRE ALARM STATION NOTE: DO NOT SUBSTITUTE THE VENDOR, OEM: TOMAR ELECTRONICS INC OEM PART NO: RMS-67-EX-PW1-PKLLP, DRAWING DEEST-CHY102-001 REV: 0, SPR ETH-068-1 REV: 0, TAG/EQUIP NO: 10-00-MP-001 THRU 016, TAG/EQUIP NO: 10-AS-01-MP-001, TAG/EQUIP NO: 10-AS-02-MP-001, TAG/EQUIP NO: 10-AS-03-MP-001, TAG/EQUIP NO: 75-00-MP-001, MODEL/MACHINE NO: EST-3
279	994977	EA	GAUGE, DIFFERENTIAL PRESSURE	GAUGE, DIFFERENTIAL PRESSURE: RANGE 0-600 KPA, DIAL SIZE 6 IN, CONNECTION NPT 1/2 IN, CASE MATERIAL SS 316, FFT: TYPE: 2 SPDT SNAP; 3 A AT 24 V; LINEAR SCALE, Mfr#: MERIAM INSTRUMENTS Mfr#: Part No: 1226-2
280	988912	EA	FAN	FAN, TYPE: MULTIBLADE, SIZE: DIA 254 MM, SPEED: 1760 RPM, ELECTRICAL RATING: 1.5 KW 440 VAC 4P 60 HZ, VOLUME RATING: 31 NM3/MIN, MOUNT: BASE ANCHORED, MATERIAL: CS ASTM A569-72; A36, FFT: ANGLE SIZE: 25 X 25 X3 MM, WITH STATIC PRESSURE: 491 PA AT 20 DEG C, DENSITY: 1.2 KG/M3, COMPLETE DEGASSIFIER FAN; MFR#: MITSUYA FAN MFG CO, MODEL: 1-1/2 FORM 1, MNFR DRG: MFO1510Y10J1
281	1600313	EA	DETECTOR, RESISTANCE TEMPERATURE	DETECTOR, RESISTANCE TEMPERATURE: TYPE MINERAL INSULATED, RESISTANCE 100 OHM, TEMPERATURE RATING 0-600 °C, SHEATH MATERIAL SS 316, WIRE 3 DUPLEX, HEAD EXPLOSION PROOF GR II A, II B, STEM SIZE U-LG 1565 (1500 MM + 65 MM THREAD) MM, PROCESS CONNECTION NIPPLE 1/2 IN NPTX 100 MM X SS 304 (SPRING LOADED), SHEATH DIAMETER 6 MM, FFT INCLUDED SUPPLY 1-1/2". 75MM ARMOURD CABLE FOR RTD TO TRANSMITTER QTY:100 MTR. DRAIN WIRE/SHEILD 7 STRANDS, ANNEALED COPPER WIRE, INNER SHEATH PVC, BLACK. ARMOUR: SERVED GALVANIZED ROUND STEEL WIRES. OUTER SHEATH PVC, OIL RESISTANCE PROPERTIES, COLOR BLACK,, MNFR: PHOENIX TEMPERATURE & ELECTROMECH. CO. W.L.L MNFR PART NO: UNK, SPECIFICATION SF20-34-15-005 REV: 0 ITEM NO: 2-16620
282	1636323	ASY	TRAP, STEAM	TRAP, STEAM, TYPE: FLOAT & THERMOSTATIC, SIZE: 4 IN, CONNECTION: FLANGE, PRESSURE RATING: 300 LB. MATERIAL: ASTM A216 GR WCB, FFT: SPIRAX SARCO FT450 STEAM TRAP: SPIRAX SARCO (4" ANSI 300 FT450 FLOAT & THERMOSTATIC STEAM TRAP, CAST STEEL BODY, PMO 450 PSIG); MAX OPERATING (PMO), MAX ALLOWABLE (PMA) OR MAX DIFFERENTIAL (PMX) THOSE NUMBERS ARE 32 BAR, 40 BAR, AND 10 BAR RESPECTIVELY; AS LONG AS THERE IS DIFFERENTIAL BETWEEN THE INLET AND OUTLET THE TRAP WILL WORK. OUR UNIT CAN HANDLE BEING IN VACUUM BUT IF THERE ISN'T A DIFFERENTIAL PRESSURE NO TRAP WILL PASS CONDENSATE; THE MAX OPERATING TEMP AND THE MAX ALLOWABLE TEMP IS 300 DEG C; MODEL: FT450, MNFR: SPIRAX SARCO LTD; TEST CERTIFICATE COMMENTS: TEST CERTIFICATE TO BE PROVIDED
283	1604038	EA	MOTOR, ELECTRIC	MOTOR, ELECTRIC: POWER RATING 1.5 KW, ELECTRICAL RATING 380 V; 3 AS 4, SPEED 1740 RPM, FRAME 90L4, MOUNT MA, ENCLOSURE IP55, INSULATION CLASS F, PHASE 3 PH, MNFR: SEW EURODRIVE MNFR PART NO: UNK, SERIAL NO: 01.174958002.0002.11, TEST CERTIFICATE COMMENTS: MTC/TEST CERTIFICATES
284	897498	EA	DIAPHRAGM	DIAPHRAGM: TYPE VENT, SIZE 2 IN, MATERIAL PTFE, FFT: PRESSURE PALLET DIAPHRAGM FOR EMERGENCY PRESSURE VENT, Mfr#: PROCTOSEAL COMPANY, USA Mfr Part No: 7810-218T-107, Model/Machine No: 7810h/3, Serial No: 234169, Tag/Equip No: 77-F5V-7247
285	1527474	EA	LAMP	LAMP: TYPE LED, PILED, WATTAGE 1.3 W, VOLTAGE 130 VDC, COLOR AMBER, STANDARD UL, FFT: FOR MV SWITCHGEAR, MNFR: LEDTRONICS MNFR PART NO: RPLB-0203-130V1402 5L, MNFR DRG 82517-1-D4 (B3-E-4001) REV: 2 ITEM NO: 43, MNFR DRG 82517-2-D4 REV: 2 ITEM NO: 42
286	676531	EA	RELAY, CONTROL	RELAY, PROTECTION: TYPE GROUND, APPLICATION ELECTRIC POWER DISTRIBUTION SYSTEM, SUPPLY 125 VDC, Mfr#: BROWN BOVERI COMPANY GERMANY, Mfr Part No: 202D5141UL
287	858952	EA	INVERTER	INVERTER: TYPE FREQUENCY CONVERTER, OUTPUT 16 A, STANDARD CE, UL, FFT: MOVIE DRIVE TYPE MC07B-0075-5A3-4-00 AND MOVU TRAC P/N 18206786 FOR PALETPAC/FOLIOPAC/THERMOPAC, OEM: BEUMER MASCHINENFABRIK GMBH OEM Part No: 50189, Mfr#: SEW-EURODRIVE Mfr Part No: 08285268, Model/Machine No: MPV60A6370-588-4-00 Mfr#: SEW-EURODRIVE
288	524031	ST	MOTOR, GEARED	MOTOR, GEARED: POWER RATING 2.2 KW, ELECTRICAL RATING 460VAC 4.2A 60HZ, PHASE THREE, OUTPUT SPEED 1715 / 132 RPM, RATIO 1715:132, GEARBOX TYPE HELICAL WORM, MOUNT SHAFT, TYPE BRAKE, FFT: 24Nm, BREAK VOLTS (BV) TORQUE (NM): 120 AC / 28; USED FOR PALLETIZER SLIDING PLATE PHASE VII, TAG # X-7104C / G - M13, Mfr#: SEW-EURODRIVE Mfr Part No: SA67/T DV100M4/BMG/VR, Serial No: 01.3072164507.0001X02
289	1551233	EA	MOTOR, ELECTRIC	MOTOR, ELECTRIC: POWER RATING: 2.2KW, 2.5HP, ELECTRICAL RATINGS: 460 V, TYPE: VENTILATOR FAN - AC MOTOR, SPEED: 2890 RPM, FRAME: 814 INNER FLANG, MOUNT: M1A, ENCLOSURE: IP55, CONNECTION LOCATION: NORMAL, INSULATION CLASS: IEC 38 / B, CASE MATERIAL: AL, TEMPERATURE CLASS: F, CLASSIFICATION: ENERGY EFFICIENCY-HIGH, PHASE: 3 PH, DIRECTION: CW, STANDARD: IEC, FG: BG FILTRATION MATADOR - DEDUSTING VENTILATOR FAN MOTOR; P/N: FCA 90 L 2/PHE (NEW), MNFR: AC-MOTOREN GMBH, P/N: FCA90L-2/H, OEM: AC-MOTOREN GMBH
290	811200	ST	BRUSH, ELECTRICAL	BRUSH, ELECTRICAL: TYPE: BRISTLE ELEMENT, MATERIAL: SILVER GOLD COMPOSITE, SIZE: WD 15 X LG 38 X HT 26.5 MM, QUANTITY PER SET: 1, CONNECTION: SCREWED; P/N: SRP-S-11, MNFR: SOHRE TURBO MACHINERY INC, MODEL: 6.355
291	1655966	EA	BRAKE	BRAKE, TYPE: MAGNET, TORQUE: 40 NM, APPLICATION: BEUMER STRETCH HOOD MACHINE; P/N: 4950429, MNFR: SEW EURODRIVE, MODEL: BESA 120AC, MNFR: SEW EURODRIVE
292	892829	EA	REGULATOR	REGULATOR: TYPE: INSTRUMENT, RATING: 0-25 PSI, CONNECTION: FNPT 1/4 IN, FFT: COMPLETE ASSEMBLED REGULATOR CONSISTS (1) ADJ SCREW: MAQ24X (2) JAM NUT SS: MAQ25X (3) SPRING RANGE DISC: IR1001A (4) SPRING HOUSING: IR400X (5) SPRING GUIDE: IR1300 (6) SPRING: SPR170X (7) BOTTOM SPRING GUIDE: IR1000 (8) DIAPHRAGM ASSY: MD0060 (9) CONTACT ROD: IRD1003 (10) O-RING: V070013 (11) BODY: IRD1007; P/N: IR04K0XA, MNFR: WELKER
293	1242870	ASY	ASSEMBLY	ASSEMBLY, TYPE: TOP COLD BAR, APPLICATION: FLUM WRAPPER; P/N: ARPAC P/N 292436A, MNFR: ARPAC, MNFR DRG: FLP-TE-AR-022-SPRM-026
294	1670799	EA	MOTOR, ELECTRIC	MOTOR, ELECTRIC: POWER RATING: 1 HP, ELECTRICAL RATING: 230/460 V 2.90/1.44 A 60HZ, TYPE: AC, SPEED: 1740 RPM, FRAME: C, MOUNT: FC, ENCLOSURE: IP54 TFC, INSULATION CLASS: THERMAL F, PHASE: 3 PH; P/N: DR80M4/FC, MNFR: SEW EURODRIVE, SERIAL: 850103802.13.13.001, MNFR: SEW EURODRIVE; TEST CERTIFICATE COMMENTS: OEM TEST CERTIFICATE
295	922845	EA	REGULATOR, PNEUMATIC	REGULATOR, PNEUMATIC: TYPE AIR FILTER, INLET PRESSURE 225 PSI, OUTLET PRESSURE 120 PSI, CONNECTION FNPT, BODY SIZE 1/4 IN, BODY MATERIAL DIE CAST AL, Mfr#: CCI CONTROL COMPONENTS INC. Mfr Part No: AFRI0, Mfr#: EXCELOM Mfr Part No: 872G-245-980
296	411444	EA	RELAY, TIME DELAY	RELAY, TIME DELAY: OPERATION 0.05SEC-300HR ON DELAY TIMER, CONTACT RATING 200-250VAC 1.5-4A, CONTACT ARRANGEMENT 2NO-2NC, ACTION DPDT, COIL VOLTAGE 24-240VAC 50/60HZ, TERMINAL CLAMP, MOUNT RAIL, STANDARD CE, CSA B300, UL 8822, FFT:, Mfr#: AEG GMBH Mfr Part No: UNKNOWN, DRAWING: 9487 E-ZK-1007 Rev. UNK, Model/Machine No: MFS Mfr#: AEG GMBH, Reference No: 910-346-631-00 Mfr#: AEG GMBH
297	881706	EA	GAUGE, LEVEL	GAUGE, LEVEL: TYPE: VISIBILE LIQUID, VISIBILE LENGTH: (157.48 IN) 4 M, CONNECTION: FLANGE 3 IN 150LB, PRESSURE RATING: 20 PSI G, SECTIONS: 3, MATERIAL: HASTELLOY C; FFT: CHAMBER STYLE: SIDE FLANGED; SPECIFIC GRAVITY: 1.3, MAX.WORKING TEMPERATURE: 50 DEG C (122 DEG F); INDICATOR TYPE: FLAG(WAFER); P/N: MII-ESF-24-01-LC-1.3-20-122-157-48-FL-MS, MNFR: JERGUSON GAGE & VALVE CO
298	1681794	EA	CARD, COMPUTER	CARD, COMPUTER: TYPE: PROCESSOR, SIZE: WD 5 X LG 7 MM; P/N: E083070, MNFR: OPSIS AB, SWEDEN
299	164992	EA	ACTUATOR, PNEUMATIC	ACTUATOR, PNEUMATIC: OPERATED AIR TO OPEN, FFT: COMPLETE, Mfr#: AUTOMAX, USA Mfr Part No: SNA300509, Drawing B00090-1G09/93 Rev: 0
300	524029	ST	MOTOR, GEARED	MOTOR, GEARED: POWER RATING 0.25 KW, ELECTRICAL RATING 460VAC 0.73A 60HZ, PHASE THREE, OUTPUT SPEED 46 RPM, RATIO 46:1680, GEARBOX TYPE HELICAL PARALLEL, MOUNT FOOT, TYPE BRAKE, FFT: 4Nm, BRAKE VOLTS - 266V, USED FOR WOODEN Pallet MAGAZINE FORK IN / OUT PHASE VII, TAG # X-7104C/G - X - M3, Mfr#: SEW-EURODRIVE Mfr Part No: R3D7T1C4-BMG
301	700517	EA	FUSE	FUSE: TYPE CURRENT LIMITING; POWER, AMPERAGE 9 A, VOLTAGE 4.8/5.08 KV, CARTRIDGE FIBRE, CONNECTION FERRULE/OFFSET BOLTED TAG, STANDARD UL, FFT: INT.CAP:80KA, Mfr#: GE (GENERAL ELECTRIC CO.) Mfr Part No: 55A212942P98B, Mfr#: POWELL ELECTRICAL MFG CO. Mfr Part No: 55A212942P98B
302	837045	EA	MODULE	MODULE: TYPE PHOTOMULTIPLIER TUBE, APPLICATION GAS CHROMATOGRAPH, Mfr#: SAA Mfr Part No: 1270003-001, Suppl: SIEMENS AG Suppl P/N: UNK
303	236043	EA	DETECTOR, RESISTANCE TEMPERATURE	RTD: TYPE SINGLE PT100, RESISTANCE 100 OHM, TEMPERATURE RATING: -30 TO 100 DEG C, WIRE 4, HEAD EXPLOSION PROOF, PROCESS CONNECTION MPT, FFT: DRIVE END, FOR MIXER MAIN S50-ME-01/201; EEXD 2C T6, Mfr#: FARREL Mfr Part No: HTAM327703P0004, Reference No: T2060 Mfr#: SCHORCH ELEKTRISCHE MASCHINEN, T2060-1XPT10034 Mfr#: DITTMER
304	809165	EA	RELAY, TIME DELAY	RELAY, TIME DELAY: OPERATION 1-30SEC ON DELAY, CONTACT RATING 120VAC 10A, CONTACT ARRANGEMENT 2NO-2NC, ACTION DPDT, COIL VOLTAGE 120VAC 60HZ, TERMINAL (8) PIN ROUND, MOUNT PLUG IN, ENCLOSURE CLOSED, STANDARD CE, Mfr#: AGASTAT Mfr Part No: 2112A45F
305	39804	EA	TACHOMETER	TACHOMETER: TYPE MODULE, RANGE 0625 HZ TO 30 KHZ, RATING 120VAC 50/60HZ 24VDC, FFT: FIELD PROGRAMMABLE, 4-20 MADC OUTPUT, 0-1 MA METER OUTPUT, ACCEPTS ACTIVE OR PASSIVE PICKUP, (4) SPDT RELAYS RATED 6 AMP @ 28 VDC OR 240 VAC, OPERATING TEMP: -10 DEG C TO 55 DEG C STANDARD NEMA 1 ENCLOSURE, AIRPAX TACHPAC 30, Mfr#: AIRPAX Mfr Part No: 177530-10
306	470189	EA	THERMOCOUPLE	THERMOCOUPLE: OVERALL LENGTH 200 INCH LONG WITH COIL INTO 7" DIA, FFT: 1/4 IN; 400 DEG CP; EOP: JM-01719/B, 0271 & 0275 SCREEN CHANGER, MDL: K-SWE-280/300, Mfr#: BARBER COLMAN, USA Mfr Part No: P011-31000-200-4-08, Mfr#: JOACHIM KREYENBORG CO. GMBH Mfr Part No: UNKNOWN, DRAWING: 52.142-3(1) Rev: 0
307	858125	EA	MOTOR, GEARED	MOTOR, GEARED: POWER RATING 0.12 KW, ELECTRICAL RATING 266/460VAC 0.34A 60HZ, PHASE 3, OUTPUT SPEED 1680/30, GEARBOX TYPE WORM, CLASSIFICATION NON HAZARDOUS,, OEM: MASCHINENFABRIK BEUMER GMBH & CO KG OEM PART NO: 44057, MNFR: SEW-EURODRIVE MNFR PART NO: TYPE 5-37-D6G3-S4-Z, TAG/EQUIP NO: 360-ME-413 / 463 MNFR: MASCHINENFABRIK BEUMER GMBH & CO KG, EQUIP MODEL NO: 607-0011 MNFR: MASCHINENFABRIK BEUMER GMBH & CO KG, EQUIP SERIAL NO: TP: 100 - 1120 / 300 - 3120 MNFR: MASCHINENFABRIK BEUMER GMBH & CO KG, TEST CERTIFICATE COMMENTS: ROUTINE MOTOR TEST CERTIFICATE
308	7174141	EA	GAUGE LEVEL	GAUGE LEVEL TYPE: METRIC SCALE INDICATOR VISIBILE LENGTH: 3500 MM CONNECTION: FLANGE 3 IN IN PRESSURE RATING: 150 LB WELD NECK RAISE FACE MATERIAL: CHAMBER: A312 316SS+PFA FFT: FLANGE MATERIAL S5316L PFA COATED STAND PIPE S5316L PFA COATED NIPPLES S5316L PFA COATED FLANGE GASKET TEFLONFLANGE BOLTING ASTM A193 GR. B 8MFLANGE NUTS ASTM A194 GR. B 8MFLANGE VALVE OFFFLANGES MATERIAL PVDF VALVES /PLUGS PVDF NIPPLES/ VENT P/N: MII-ESF-24-01-TC-1.72-0-120-137.795-FL-MS MNFR: JERGUSON GAGE & VALVE CO. DRAWING: MII-4360
309	7351008	ST	Measuring and observing and testing instruments	METER TYPE: SOUND LEVEL RANGE: 30 TO 140 DB READOUT: LCD P/N: SP-DL-2-1/3 MNFR: REDA (FIRE & HAZARD DEVISION) TEST CERTIFICATE COMMENTS: TEST CERTIFICATE NEEDED
310	7353392	EA	Measuring and observing and testing instruments	TESTER TYPE: CONDUCTANCE ANALYZER RANGE: 0.9 - 30 V DC APPLICATION: BATTERIES FFT: INCLUDING 6 PACK THERMAL PRINTER PAPER IR PRINTER WITH CHARGER (FOR MDX-700HD) LEAD STUD ADAPTER SET CABLE LENGTH:15 FT/455CM MDX-700HD: 19.5CM X 10CM X 5CM VENDOR : MIDTRONICS MDX-700HD SOFTWARE (INSTALLED) MANUAL STUD ADAPTERS 15FT CABLE SET TOOL BAG CATALOGUE: MDX-700HD TEST CERTIFICATE COMMENTS: YES
311	7364224	EA	Pressure transmitters	TRANSMITTER PRESSURE RANGE: 0-600 KPA TYPE: EXPLOSION PROOF CONNECTION: FNPT 1/4 IN OUTPUT: FOUNDATION FIELDBUS SUPPLY: 9-32 V DC ELECTRICAL CONNECTION: FNPT 1/2 IN 2 CONNECTIONS AND BLIND PLUG BODY MATERIAL: SS JIS G5121 GR SCS14A DIAPHRAGM MATERIAL: HASTELLOY C-276 MOUNT: PIPE 2 IN CLASSIFICATION: NEMA 4X/7 CLASS I DIVISION 2 GROUP B C & D STANDARD: FM FFT: DIGITAL COMMUNICATION PROCESS BENZENE STRIPPER DESIGN PRESSURE: 6 BAR DESIGN TEMPERATURE: 135 DEG C
312	7243225	EA	FAN	FAN: TYPE COOLING SPEED 890 RPM SIZE 19.5 IN MOUNT HORIZONTAL CLASSIFICATION CL1 DIV2 GR C & D MATERIAL PLASTIC MOUNT OF BLADES 11 APPLICATION MOTOR FFT: FOR BALDOR MOTOR NO. 20A026-0137 MNFR: BALDOR ELECTRIC CO MNFR PART NO: 18FN3000004
313	7229110	EA	RECEPTACLE ELECTRICAL	RECEPTACLE ELECTRICAL: TYPE SURFACE MOUNT SPLASHPROOF POLE 2P# WIRE 3 WIRE GROUNDING ELECTRICAL RATING 220-250VAC 30-32A STANDARD IEC. 60309 FFT: WITH BOX CLASS: IP44 BODY MATERIAL: NIKON COLOR: BLUE OPERATING TEMP.: -25 DEG C TO 20 DEG C Mfr#: INTERNATIONAL CONFIGURATION/IN Mfr Part No: 888-1114-N5
314	7364707	KIT	Temperature transmitters	SENSOR TEMPERATURE TYPE: BODY TEMP MONITOR DEVICE STYLE DESIGNATOR: REAL-TIME ACCURATE OPERATING TEMPERATURE: ACCURACY + 26 °C OUTPUT SIGNAL: ANTI- AND BLUETOOTH WITH AUTO DATA TRANSMISSION FFT: INCLUDES 6 CORE SENSOR 1 CHARGING BAY STATION1 CHEST STRAP 1 ARM STRAP AND BOX OF 24 MEDICAL GRADE ADHESIVE PATCHES REFERENCE: CORE - TEAM BUNDLE MNFR: CORE-SENSORS
315	7364806	EA	Gas detectors	DETECTOR GAS TYPE: LEAK RANGE: 10 TO +40 °C POTENTIAL: RECHARGEABLE LI-ION BATTERY FFT: ACCESSORIES: GAS LEAK DETECTOR LD239 2702-19340 BATTERY FOR LD239 2702-19341 USB CABLE 2702-19331 SAMPLE FILTER 2702-19333 REFERENCE FILTER: LD239-19334 P/N: LD239 MNFR: GLO SCIENCES INC
316	7359703	EA	Circuit breakers	BREAKER CIRCUIT AMPERAGE: 150 A VOLTAGE: 600 V INTERRUPT CAPACITY: 65 KA POLE: 3 P TYPE: CASE RATING PLUG 125A MOUNT: BOLT ON/PANEL FRAME: E TEMPERATURE RATING: N/A CLASSIFICATION: UL 489 P/N: SELA36A0150 MNFR: ARABIAN POINT EIGHT POWER
317	7355776	EA	Measuring and observing and testing instruments	METER TYPE: PH BENCHTOP RANGE: 0-14 PH READOUT: DIGITAL P/N: STARA2119 MNFR: THERMO CATALOGUE: ORION STAR™ A211 BENCHTOP PH METER
318	7277962	ST1	TESTER	TESTER: TYPE VACUUM INTERRUPTER TESTER APPLICATION FOR TESTING THE INTERRUPTER VACUUM INTEGRITY FFT: OPERATING VOLTS 115/230 V AC (SWITCHABLE) 50/60 HZ POWER CONSUMPTION 69 VA (MAX) DIM: 250 X 210 X 125 MM OUTPUT STANDARD VOLTAGES SWITCHABLE 10 14 25 40 AND 60 KV DC ACCURACY 0 TO -15% PERMANENTLY MOUNTED CABLE SET 5 M (16 FT) GROUND CABLE AND TRANSPORT CASE (GG-00030) MNFR: MEGGER MNFR PART NO: VIDAR

319	7155012	M	CABLE ELECTRICAL	CABLE CONTROL: CONDUCTOR 2 PAIR CU CONDUCTOR. RATING 18 AWG INSULATION XLPE TYPE INSTRUMENT SIGNAL FFT: 300V INSULATION OA & IS SHIELDED Mfr: MIDDLE EAST SPECIALIZED CABLES CO Mfr Part No: UNK
320	7358260	EA	Limit switches	SWITCH LIMIT CONTACT RATING: 15A AT 250VAC TYPE: MICRO ACTUATOR: SHORT HINGE ROLLER LEVER ACTION: SNAP ACTION ROLLER LI MOMENTARY CONTACT ARRANGEMENT: SPDT ENCLOSURE: PLASTIC SIZE: LG 37.8 X WD 10.3 X HT 18.8 MM P/N: V-155-1C25 MNFR: OMRON ELECTRONIC COMPONENTS TEST CERTIFICATE COMMENTS: TEST CERTIFICATE REQUIRED
321	7352576	EA	Indicator or pilot lights	INDICATOR LIGHT TYPE: LED COLOR: GREEN/RED/YELLOW MOUNTING FACILITY: SCREW CONNECTION TYPE: PLUG IN/TERMINAL SPECIAL FEATURES: RATING IP68 P/N: E5813 GRV.B
322	7351208	SE	Clamps	CLAMP TYPE: SWIVEL LOCK SIZE: M8 X90 MM MATERIAL: GALVANIZE APPLICATION: PP PLANT GRATING PLATFORM FFT: SET OF 4 PCS CONSISTING OF: UPPER CLAMP LOWER CLAMP SQUARE NUT & HEX BOLT 3-1/2 INCH (90MM) LONG GALVANIZED. SUITABLE FOR BAR GRATING P/N: GRATING CLAMP M8X90MM OEM: TAMIMI COMPANY
323	7297725	EA	BATTERY	BATTERY: TYPE LEAD ACID BATTERY VOLTAGE 12 V SIZE WD 6.8 X LG 13 X HT 9.4 IN CURRENT CAPACITY 105 AH MNFR: AC DELCO USA MNFR PART NO: 52000
324	7360341	EA	Level or float switches	SWITCH LEVEL CONTACT RATING: 5 A TYPE: FLOATLESS RANGE: 0-100 OHM POWER SOURCE: 120 VAC ACTION: SPDT CONTACT ARRANGEMENT: 1NO 1NC METHOD OF ACTUATION: LEVEL SIZE: LG 57.5 MM ENCLOSURE: IP 30 CLASSIFICATION: NON CLASSIFIED APPLICATION: LEVEL CONTROL STANDARD: IEC FFT: CDIL VOLTAGE: 120 V AC P/N: AFS-1 MNFR: ANLY ELECTRONICS CO. LTD
325	7087689	EA	REFRIGERATOR	REFRIGERATOR: CAPACITY 5 FT3 Mfr: LG ELECTRONICS Mfr Part No: UNK Suppl: MOHAMMAD AL-MOJIL GROUP Suppl P/N: UNK Model/Machine No: 131
326	7361795	EA	Dry cell batteries	BATTERY DRY CELL TYPE: SEALED LEAD ACID VOLTAGE: 6 V AMP HOURS: 1.3 AH FFT: CYCLE USE: 7.2-7.4V STANDBY USE: 6.8-6.9V INITIAL CURRENT: LESS THAN 0.39V MODEL: GB 6-1.3 MNFR: BSB POWER COMPANY LIMITED
327	7355272	EA	Cable gland connector	GLAND CABLE TYPE: FLAME PROOF SIZE: 20 MM MATERIAL: BRASS/NICKEL PLATED HUB SIZE: 20.5 MM CONNECTION: MPT CLASSIFICATION: EEXD IIC EEXE II FFT: PLANT CABLE WIRINGS GLAND FOR CABLEGENERAL ELECTRICAL USE IN PLANT
328	7364242	EA	Fiber optic cable	CABLE FIBER OPTIC TYPE: STRANDED LOOSE TUBE FIBER COUNT: 24 * SINGLE JACKETSINGLE ARMOR DIAMETER: OVER JACKET 11.50 MM FFT: STANDARDS : ANSI/ICEA 5-87-640 GEL-FREE OUTDOOR STANDARD24 CORE 1 EA IS 500 M (AS PER OEM ROLL SIZE) MODEL: D-024-LA-8W-F12N 5
329	7362419	EA	Telecommunications cable	CABLE COMMUNICATION CONDUCTOR: (2) CORE CONDUCTOR RATING: 80 V TYPE: CHARGING INSULATION: PLASTIC REFERENCE: G7-5020-0005 MNFR: BARTEC P/N: 45
330	7345669	ASY	Electrical boxes	BOX JUNCTION TYPE: WEATHER PROOF MATERIAL: 316 STAINLESS STEEL SIZE: WD 372 X HT 448 X DP 203 MM POTENTIAL: 600 V ENCLOSURE RATING: NEMA 4X FFT: TERMINAL 600V 16AWG COMPLETE ASSEMBLY WITH MOUNTING PLATE AND BRACKET WITH BREATHER /DRAIN 316 SSBOLT/NUT/WASHER SS 316
331	7364786	EA	Lighting Fixtures and Accessories	LIGHT UNIT TYPE: DEEP PARABOLIC SOFTBOX SIZE: 90 CM / 35 IN FFT: SOFT LIGHT WITH AN EDGE OF CRISPNESS FOCUSED LIGHT OFFERS DIRECTIONAL CONTROL INCREASED DIMENSION DETAIL AND CONTRAST REDUCED SPILL LIGHT EASY FEATHERING BOWENS S-TYPE SPEED RING MODEL: P90L MNFR: GODOX
332	7364815	EA	Lighting Fixtures and Accessories	LIGHT UNIT TYPE: CAMERA SIZE: ALTEZZA MAX 180 CM AND ROTAZIONE 180 MATERIAL: ALLUMINIO P/N: LB02 MNFR: GODOX PHOTO EQUIPMENT CO. LTD
333	7364788	EA	Lighting Fixtures and Accessories	LIGHT UNIT TYPE: WHEELED LIGHT STAND AND TRIPOD CARRYING BAG SIZE: 44.9 IN FFT: FOR STANDS AND TRIPODS UNDER LENGTH: 44.9 IN ZIPPER CLOSURE DUAL CONNECTING TOP STRAP HANDLES TOP HULL HANDLE BUILT-IN WHEELS RUBBER FOOT FOR UPRIGHT STANDING NYLON CONSTRUCTION P/N: CB-01 MNFR: GODOX PHOTO EQUIPMENT CO. LTD
334	7348157	EA	Weight measuring instruments	SCALE WEIGH TYPE: PRECISION BALANCE CAPACITY: 1210 G P/N: XSR12035 MNFR: METTLER TOLEDO INTERNATIONAL INC
335	7196155	ST	VACUUM CLEANER	VACUUM CLEANER: TYPE HANDHELD PORTABLE CORDLESS AND RECHARGEABLE CAPACITY 1/2 GAL FFT: TOOL WEIGHT: 3.6 LB / 1.5 KG HOSE DIA: 1-1/2 IN C/W 18V NI-CD BATTERY AND FILTER WITH 1 SPARE FILTER (DV 5154 H) Mfr: DEWALT Mfr Part No: DC 515 X
336	7360733	EA	Flow switches	SWITCH FLOW RANGE: ADJUSTABLE ACTION: FAIL OPEN CONTACT RATING: 120/240 V CONNECTION: 1 IN NPT MATERIAL: STAINLESS STEEL/ BRASS P/N: 320610 MNFR: MCDONNELL & MILLER MODEL: F254 MNFR: MCDONNELL & MILLER
337	7354430	EA	Signage	SIGN TYPE: 3-DIGIT LED DISPLAY DESIGNATION: DIGITAL SPEED TRAFFIC SIGN SENSOR WITH EMOJI BASIC SHAPE STYLE: RECTANGULAR SIZE: W 800 X H 2200 MM MATERIAL: ALUMINIUM ATTACHMENT METHOD: CLAMP COLOR: BLACK BACKGROUND INSCRIPTION COLOR: IT SHOWS GREEN COLOR TEXT FOR NON-SPEEDING VEHICLE BUT SHOWS RED COLOR TEXT FOR SPEEDING VEHICLE FFT: POWER SUPPLY: AC 110-240V OR DC12V SOLAR MODULE(OR CUSTOMIZED) RADAR TYPE: DOPPLER RADAR DISPLAY MODE: 3-DIGIT LED DISPLAY(1-199KM/H)
338	7347904	ST	Hardware or telephony adapters	ADAPTOR COMMUNICATION TYPE: STEREO MIC CONDUCTOR: COPPER APPLICATION: HEROS/87/6/5 BLACK & HEROS SESSION FFT: 3.5MM MIC/LINE AUDIO INPUT USB PASS-THROUGH FOR CAMERA CHARGING COMPATIBLE WITH THE HEROS BLACK HEROS BLACK HEROT BLACK HEROT BLACK HEROS BLACK AND HEROS SESSION. P/N: GOPRO PRO 3.5MM MIC ADAPTER
339	7204471	EA	LIGHTER	LIGHTER: TYPE CIGARETTE FFT: 110 VAC SUPPLY WALL MOUNTED UNIT WITH TIMER FOR INSTALLATION BACK INTO WALL CAVITY DIMENSIONS: WD. 385 X HT 210 X 55 MM RAISED ANGLED SIDES FLAMELESS WATER AND WEATHER PROOF UNIT IP 65 TO BE PROVIDED WITH ADDITIONAL TWO SPARE LONG LASTING ELEMENTS AND A WARRANTY Mfr: OZILITE Mfr Part No: ACL110WMT INSTALLATION AND INSTRUCTION MANUALS TO BE PROVIDED
340	7364956	EA	Water purification equipment	PURIFIER TYPE: AIR PURIFIER AND HUMIDIFIER CONNECTION: POWER SUPPLY: 220-240 V AC MATERIAL: PLASTIC MODEL: AC2729/90 MNFR: PHILIPS
341	7359138	EA	Electrical Sys and Light and Comp and Access and Supplies	POUCH TYPE: ID CARD COVER SIZE: 54 X 90 MM MATERIAL: PLASTIC P/N: Z_0009 / T-014V MNFR: INDUSTRIAL SUPPORT SERVICES SPECIFICATION: 54 X 90MM REV: 1 POS: 1 MNFR: INDUSTRIAL SUPPORT SERVICES
342	7352617	EA	Cameras	CAMERA TYPE: 4K HDR VIDEO FILM: CAPTURE FROM 1-60 SECONDS FOCUS: 40X MEGA PIXEL QUANTITY: MORE THAN 30 MEGA PIXELS RESOLUTION: 960FPS MEMORY CAPACITY: 128 GB POWER SUPPLY: 1 LITHIUM BATTERY COMPATIBILITY: GP-VPT2BT P/N: ZV-1 VLOG MNFR: SONY CORP
343	7352570	ST	Lighting accessories	LIGHT TYPE: DANGER LIMET LIGHT VOLTAGE: 10-80 V DC WATTAGE: 1-5 W COLOR: BLUE OR RED CLASSIFICATION: DANGER LIGHT SIZE: 2.5 M FFT: THE DANGER LIGHT EMITS A RED/BLUE BEAM ON THE FLOOR TO KEEP PEDESTRIANS AWAY PREVENTING FOOT INJURY OR COLLISION FROM REAR END SWING THE DANGER LIGHT SYSTEM OFFERS A COMPLETE PEDESTRIANS WARNING SYSTEM FOR WAREHOUSE. LIGHT SOURCE 6 PCS HIGH POWER LED'S . LUX : 200LUX ON THE GROUND AT 2.5M LIFETIME > 50000 HRS WORKING TEMPERATURE : 40 -80 DEGC MNFR: SHARPEAGLE TECHNOLOGY
344	7352602	ST	Lighting accessories	LIGHT TYPE: SPOT LIGHT VOLTAGE: 10-80 V DC WATTAGE: 3 W COLOR: RED OR BLUE SIZE: 3-5 M FFT: FORKLIFT SPOT SAFETY LIGHT WILL PROJECT A BLUE APERTURE IN THE AREA ABOUT 3 TO 5 METERS FROM THE FORKLIFT TO REMIND THE PEDESTRAIN TO RETREAT OF THE FORKLIFT TO PREVENT ACCIDENT LIGHT SOURCE HIGH POWER LED 1 PCS 3W LIFETIME > 30000 HOURS WORKING TEMPERATURE 45- 85 DEGC P/N: N/A MNFR: SHARPEAGLE TECHNOLOGY
345	7354544	EA	Flashlight	FLASHLIGHT CELL: LITHIUM SIZE NUMBER: 136 X 26.4 X 25.4 MM MATERIAL: METALIC TYPE: SAFETY POWER RATING: 1600 LUMENS FFT: WITH ACCESSORIES (BATTERY CHARGER ADAPTER HOOK ETC.) LIGHTING RANGE 283 METERS POWERED BY RECHARGEABLE LITHIUM BATTERY WITH A CAPACITY OF 21700 FAST CHARGING FOR 4 HOURS WITH USB CHARGING PORT. MODEL: PD36R-E01 V2.0
346	7352622	ST	Lighting accessories	LIGHT TYPE: ARC HIGH POWER LED VOLTAGE: 10-80 V DC WATTAGE: 3 W COLOR: RED BLUE OR GREEN FFT: FORKLIFT ARC SAFETY LIGHT HAS BEEN DESIGNED SPECIFICALLY FOR THE REAR OF THE FORKLIFT WITH SMOOTH ROUND EDGES. MIMICKING THE BACK OF THE FORKLIFT WITH SIMILAR ROUND COUNTERWEIGHT DESIGN SO PEDESTRIANS WILL KNOW IMMEDIATELY THE DIRECTION OF THE VEHICLE AND WHICH WAY THE OPERATOR IS FACING LIGHT SOURCE : HIGH POWER LED'S 6 PCS 3W LIFE TIME >50000HOURS BEAM: ARC BREAM. WORKING TEMPEATURE 45-82 DEGC. P/N: N/A MNFR: SHARPEAGLE TECHNOLOGY
347	7188182	EA	METER	METER: TYPE BENCH TOP CONDUCTIVITY/TDS/TEMPERATURE METER READOUT DIGITAL APPLICATION MEASUREMENT OF CONDUCTIVITY AND TDS FFT: WITH 10 READING MEMORY FACILITY 230V 50/60HZ 0 TO 1999US/MS 0 TO 1999MG/L 0 TO 199.9G/L 210MM X 250MM X 60MM MNFR: JENWAY MNFR PART NO: 451001 MODEL/MACHINE NO: 4510 TEST CERTIFICATE COMMENTS: CERTIFICATE OF THE CONDUCTIVITY ELECTRODE TO ACCOMPANY THE METER
348	7291424	EA	BATTERY STORAGE	BATTERY STORAGE: MNFR: POWER-SONIC CORPORATION M PS12280
349	7312143	EA	MONITOR	MONITOR: TYPE FUME HOOD RANGE 50-250 FT/MIN POWER SOURCE 100-220 V AC SIZE WD 8 X LG 15 X HT 4.6 CM APPLICATION FUME HOOD FLOW MONITOR FFT: MONITOR: FUME HOOD FLOW MONITOR MANUFACTURER : TEMPRATURE ELECTRONIC LIMITED MNFR PART NO: AFA1000